

Product Name: MOBILTRANS MBT 75W-90

Revision Date: 08 Apr 2019 SDS Number: 2006260XCN

Issue Date: Version:4.01

# SAFETY DATA SHEET

# SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT

Product Name: MOBILTRANS MBT 75W-90

Product Description: Synthetic Base Stocks and Additives

Product Code: 201520506510, 550319-80
Recommended Use: Manual transmission fluid

#### COMPANY IDENTIFICATION

Supplier: ExxonMobil (China) Investment Co., Ltd.

17/F., Metro Tower 30 Tian Yao Qiao Road Shanghai 200030 China

 24 Hour Emergency Telephone
 (+86)
 0532-83889090

 Supplier General Contact
 (+86)
 021-24076000

E-Mail lubricants-sds@exxonmobil.com

FAX 400 1200 526

# SECTION 2 HAZARDS IDENTIFICATION

# **EMERGENCY OVERVIEW:**

Physical State: Liquid Colour: Amber Odour: Characteristic

H412: Harmful to aquatic life with long lasting effects.

High-pressure injection under skin may cause serious damage. Excessive exposure may result in eye, skin, or respiratory irritation.

The hazard classification for this material is in accordance with the General Rules for Classification and Hazard Communication of Chemicals (GB 13690-2009).

# CLASSIFICATION:



Product Name: MOBILTRANS MBT 75W-90

Revision Date: 08 Apr 2019 SDS Number:2006260XCN

Issue Date: Version: 4.01

Acute aquatic toxicant: Category 3. Chronic aquatic toxicant: Category 3.

LABEL:

Symbol: No Symbol

Signal Word: No Signal Word

Hazard Statements:

Environmental: H412: Harmful to aquatic life with long lasting effects.

#### Precautionary Statements:

Prevention: P261: Avoid breathing mist / vapours. P272: Contaminated work clothing should not be allowed out of the workplace. P273: Avoid release to the environment. P280: Wear protective gloves. Response: P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P333 + P313: If skin irritation or rash occurs: Get medical advice/attention. P362 + P364: Take off contaminated clothing and wash it before reuse.

Disposal: P501: Dispose of contents and container in accordance with local regulations.

Contains: SUBSTITUTED THIADIAZOLE, AMINES, C12-14-TERT-ALKYL May produce an allergic reaction.

Other hazard information:

#### PHYSICAL / CHEMICAL HAZARDS

No significant hazards.

# HEALTH HAZARDS

High-pressure injection under skin may cause serious damage. Excessive exposure may result in eye, skin, or respiratory irritation.

### ENVIRONMENTAL HAZARDS

No additional hazards.

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

#### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

This material is defined as a mixture.



Product Name: MOBILTRANS MBT 75W-90

Revision Date: 08 Apr 2019 SDS Number:2006260XCN

Issue Date: Version: 4.01

#### Hazardous Substance(s) or Complex Substance(s) required for disclosure

Name	CAS#	Concentration*	GHS Hazard Codes
5-(DODECYLDITHIO)-1,3,4-THIADIAZOLE-2(3H)-THIONE	50530-43-3	0.1 - < 1%	Н317
ALKYL DITHIOPHOSPHATE	108464	0.1 - < 1%	H400(M factor 1), H410(M factor 1)
AMINES, C12-14-TERT-ALKYL	68955-53-3	0.1 - < 1%	H302, H311, H317, H330(2), H314(1B), H400(M factor 1), H410(M factor 1)

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### SECTION 4 FIRST AID MEASURES

# FIRST AID:

#### INHALATION

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

### SKIN CONTACT

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

# EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

# INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

#### IMPORTANT SYMPTOMS AND HEALTH EFFECTS

Local necrosis as evidenced by delayed onset of pain and tissue damage a few hours after injection. Itching and rash from allergic skin reaction.

# ADVICE TO PROTECT RESCUER

Please refer to Section 8 for personal protection information.

# NOTE TO PHYSICIAN

The need to have special means for providing specific and immediate medical treatment available in the workplace is not expected.



Product Name: MOBILTRANS MBT 75W-90

Revision Date: 08 Apr 2019 SDS Number:2006260XCN

Issue Date: Version: 4.01

#### SECTION 5 FIRE FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Inappropriate Extinguishing Media: Straight streams of water

#### SPECIAL HAZARD WHEN ON FIRE

In case of fire, see below for hazardous combustion products. Containers exposed to excessive heat from a fire may rupture.

#### FIRE FIGHTING INSTRUCTIONS AND PROTECTIVE MEASURES

#### FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Hazardous Combustion Products:** Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulphur oxides

# FLAMMABILITY PROPERTIES

Flash Point [Method]: >200 C (392 F) [ ASTM D-92]

Flammable Limits (Approximate volume % in air): LEL: 0.9 UEL: 7.0

Autoignition Temperature: N/D

# SECTION 6 ACCIDENTAL RELEASE MEASURES

### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

### PROTECTIVE MEASURES

Avoid contact with spilled material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of



Product Name: MOBILTRANS MBT 75W-90

Revision Date: 08 Apr 2019 SDS Number:2006260XCN

Issue Date: Version: 4.01

the emergency responders.

#### ENVIRONMENTAL PRECAUTIONS

Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

### SPILL MANAGEMENT

Land Spill: Stop leak if you can do so without risk. Recover by pumping or with suitable absorbent.

**Water Spill:** Stop leak if you can do so without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

### SECTION 7 HANDLING AND STORAGE

#### HANDLING

Avoid contact with skin. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or earthing procedures. However, bonding and earthing may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

Static Accumulator: This material is a static accumulator.

#### **STORAGE**

The type of container used to store the material may affect static accumulation and dissipation. Do not store in open or unlabelled containers. Keep away from incompatible materials.

# SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION



Revision Date: 08 Apr 2019 SDS Number:2006260XCN

Issue Date: Version: 4.01

Exposure limits/standards for materials that can be formed when handling this product: When mists / aerosols can occur, the following are recommended: 5 mg/m3 - ACGIH TLV (inhalable fraction).

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

#### ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

#### PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No special requirements under ordinary conditions of use and with adequate ventilation. Particulate filter when appropriate.

For high airborne concentrations, use an approved supplied—air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended. Nitrile, Viton

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

Revision Date: 08 Apr 2019 SDS Number:2006260XCN

Issue Date: Version: 4.01

Chemical/oil resistant clothing is recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

#### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

#### GENERAL INFORMATION

Physical State: Liquid

Colour: Amber

Odour: Characteristic Odour Threshold: N/D

# IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15 C): 0.849

Flash Point [Method]: >200 C (392 F) [ ASTM D-92]

Flammable Limits (Approximate volume % in air): LEL: 0.9 UEL: 7.0

Flammability (Solid, Gas): N/A Autoignition Temperature: N/D

Boiling Point / Range: > 316 C (600 F) Vapour Density (Air = 1): > 2 at 101 kPa

**Vapour Pressure:** < 0.013 kPa (0.1 mm Hg) at 20  $^{\circ}$  C

Evaporation Rate (n-butyl acetate = 1): N/D

pH: N/A

Log Pow (n-Octanol/Water Partition Coefficient): > 3.5

Solubility in Water: Negligible

**Viscosity:** 95 cSt (95 mm2/sec) at 40 C | 14.5 cSt (14.5 mm2/sec) at 100 C [DIN 51562]

Freezing Point: N/D Melting Point: N/A

Decomposition Temperature: N/D

Oxidizing Properties: See Hazards Identification Section.

# OTHER INFORMATION



Revision Date: 08 Apr 2019 SDS Number: 2006260XCN

Issue Date: Version: 4.01

**Pour Point:** -42 C (-44 F)

# SECTION 10 STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization will not occur.

CONDITIONS TO AVOID: Excessive heat. High energy sources of ignition.

MATERIALS TO AVOID: Strong oxidisers

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

# SECTION 11 TOXICOLOGICAL INFORMATION

# INFORMATION ON TOXICOLOGICAL EFFECTS

<u>Hazard Class</u>	Conclusion / Remarks
Inhalation	
Acute Toxicity: No end point data for	Minimally Toxic. Based on assessment of the components.
material.	
Irritation: No end point data for	Negligible hazard at ambient/normal handling temperatures.
material.	
Ingestion	
Acute Toxicity: No end point data for	Minimally Toxic. Based on assessment of the components.
material.	
Skin	
Acute Toxicity: No end point data for	Minimally Toxic. Based on assessment of the components.
material.	
Skin Corrosion/Irritation: No end point	Negligible irritation to skin at ambient temperatures.
data for material.	Based on assessment of the components.
Еуе	
Serious Eye Damage/Irritation: No end	May cause mild, short-lasting discomfort to eyes. Based on
point data for material.	assessment of the components.
Sensitisation	
Respiratory Sensitization: No end point	Not expected to be a respiratory sensitizer.
data for material.	
Skin Sensitization: No end point data	Contains a substance that may cause skin sensitization.
for material.	Based on assessment of the components.
Aspiration: Data available.	Not expected to be an aspiration hazard. Based on physico-
	chemical properties of the material.
Germ Cell Mutagenicity: No end point	Not expected to be a germ cell mutagen. Based on assessment
data for material.	of the components.
Carcinogenicity: No end point data for	Not expected to cause cancer. Based on assessment of the
material.	components.



Product Name: MOBILTRANS MBT 75W-90

Revision Date: 08 Apr 2019 SDS Number: 2006260XCN

Issue Date: Version: 4.01

Reproductive Toxicity: No end point	Not expected to be a reproductive toxicant. Based on
data for material.	assessment of the components.
Lactation: No end point data for	Not expected to cause harm to breast-fed children.
material.	
Specific Target Organ Toxicity (STOT)	
Single Exposure: No end point data for	Not expected to cause organ damage from a single exposure.
material.	
Repeated Exposure: No end point data	Not expected to cause organ damage from prolonged or
for material.	repeated exposure. Based on assessment of the components.

#### TOXICITY FOR SUBSTANCES

NAME	ACUTE TOXICITY
AMINES, C12-14-TERT-ALKYL	Dermal Lethality: LD 50 251 mg/kg (Rat); Inhalation
	Lethality: 4 hour(s) LC50 1.19 mg/l (Vapour) (Rat); Oral
	Lethality: LD 50 612 mg/kg (Rat)

#### OTHER INFORMATION

For the product itself:

Repeated and/or prolonged exposure may cause irritation to the skin, eyes, or respiratory tract. Contains:

Synthetic base oils: Not expected to cause significant health effects under conditions of normal use, based on laboratory studies with the same or similar materials. Not mutagenic or genotoxic. Not sensitising in test animals and humans.

#### IARC Classification:

The following ingredients are cited on the lists below: None.

--REGULATORY LISTS SEARCHED--

1 = IARC 1 2 = IARC 2A 3 = IARC 2B

### SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

#### **ECOTOXICITY**

 ${\tt Material -- Expected \ to \ be \ harmful \ to \ aquatic \ organisms. \ May \ cause \ long-term \ adverse \ effects }$ 



Product Name: MOBILTRANS MBT 75W-90

Revision Date: 08 Apr 2019 SDS Number:2006260XCN

Issue Date: Version: 4.01

#### MOBILITY

Base oil component — Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

#### SECTION 13 DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

#### NATIONAL CATALOGUE OF HAZARDOUS WASTES

HW49 - Other Waste Materials

#### DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Protect the environment. Dispose of used oil at designated sites. Minimize skin contact. Do not mix used oils with solvents, brake fluids or coolants.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

# SECTION 14 TRANSPORT INFORMATION

 $\hbox{\it China List of Dangerous Goods (GB 12268 - 2012)} : \hbox{\it Not Regulated for Land Transport}$ 

# INTERNATIONAL CLASSIFICATION FOR TRANSPORT

SEA (IMDG): Not Regulated for Sea Transport according to IMDG-Code

Marine Pollutant: No



Revision Date: 08 Apr 2019 SDS Number:2006260XCN

Issue Date: Version: 4.01

AIR (IATA): Not Regulated for Air Transport

#### SECTION 15 REGULATORY INFORMATION

The hazard classification for this material is in accordance with the General Rules for Classification and Hazard Communication of Chemicals (GB 13690-2009).

#### REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS

The General Rules for preparation of precautionary label for Chemicals (GB 15258-2009): Regulated

Law of the People's Republic of China on Prevention and Control of Environmental Pollution by Solid Waste: See Disposal Considerations section.

Listed or exempt from listing/notification on the following chemical inventories (May contain substance(s) subject to notification to the EPA Active TSCA inventory prior to import to USA): AICS, DSL, IECSC, KECI, PICCS, TCSI, TSCA

Special Cases:

Inventory	Status	
ISHL	Not determined	

# SECTION 16 OTHER INFORMATION

#### N/D = Not determined, N/A = Not applicable

# KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

H302: Harmful if swallowed; Acute Tox Oral, Cat 4

H311: Toxic in contact with skin; Acute Tox Dermal, Cat 3

H314(1B): Causes severe skin burns and eye damage; Skin Corr/Irritation, Cat 1B

H317: May cause allergic skin reaction; Skin Sensitization, Cat 1

H330(2): Fatal if inhaled: Acute Tox Inh, Cat 2

H400: Very toxic to aquatic life; Acute Env Tox, Cat 1

H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1

#### THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

China regulatory reference- Header information was added.

Composition: Component Table information was modified.

SDS Number Header information was added.

Revision Number- Header information was added.



Product Name: MOBILTRANS MBT 75W-90

Revision Date: 08 Apr 2019 SDS Number:2006260XCN

Issue Date: Version: 4.01

Section 01: Company Contact Methods information was modified.

Section 01: Emergency Overview - Header information was added.

Section 01: Preparation Date - Header information was added.

Section 01: Product Code information was modified.

Section 01: Product Identification Product Name information was added.

Section 01: Product Identification Product Name information was deleted.

Section 02: GHS Sensitizer Statement information was modified.

Section 04: Advice for the rescuer - Header information was added.

Section 04: Advice for the rescuer information was added.

Section 04: First Aid Measures - Header information was added.

Section 04: First Aid Notes - Header information was added.

Section 04: First Aid Notes information was added.

Section 04: Most Important Symptoms - Header information was added.

Section 04: Symptoms and Effects information was added.

Section 05: Fire Fighting Instructions - Header information was added.

Section 05: Fire Fighting Measures - Special Hazards - Header information was added.

Section 05: Fire Fighting Measures - Special Hazards information was added.

Section 11 Substance Toxicology table information was modified.

Section 11: Other Health Effects information was modified.

Section 12: information was modified.

Section 15: National Chemical Inventory Listing information was modified.

Section 15: Special Cases Table information was added.

Section 16: HCode Key information was modified.

\_\_\_\_\_

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

(AP Core)

\_\_\_\_\_

DGN: 2006260XCN (548883)

\_\_\_\_\_\_



Product Name: MOBILTRANS MBT 75W-90

Revision Date: 08 Apr 2019 SDS Number: 2006260XCN

Issue Date: Version:4.01

\_\_\_\_\_