

# SAFETY DATA SHEET

<b>SECTION 1</b>	<b>IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING</b>
------------------	-----------------------------------------------------------------------------------

As of the revision date above, this SDS meets the regulations in the United Kingdom & Ireland.

## 1.1. PRODUCT IDENTIFIER

**Product Name:** MOBILTHERM 603  
**Product Description:** Severely Treated Base Oils  
**Product Code:** 201560802010, 680512-60

### Registration Name:

Distillates (petroleum), solvent-dewaxed heavy paraffinic  
Distillates (petroleum), hydrotreated heavy paraffinic

**Identification Number:** (CAS #)64742-65-0; (CAS #)64742-54-7

### Registration Number:

01-2119471299-27  
01-2119484627-25

## 1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

**Intended Use:** Heat transfer

### Identified Uses:

Lubricants - Industrial  
Lubricants - Professional (Low Release)  
Lubricants - Professional (High Release)  
Lubricants - Consumer (Low Release)  
Lubricants - Consumer (High Release)

See Section 16 for list of REACH Use Descriptors for Identified Uses shown above.

**Uses advised against:** This product is not recommended for any industrial, professional or consumer use other than the Identified Uses above.

## 1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

**Supplier:** EXXONMOBIL MARINE LIMITED  
ERMYN HOUSE  
MAILPOINT 31, ERMYN WAY  
KT22 8UX LEATHERHEAD  
United Kingdom

**Supplier General Contact:**  
**E-Mail:**

(UK) (+44) (0) 1372 222 000  
sds.uk@exxonmobil.com

Product Name: MOBILTHERM 603  
Revision Date: 12 Dec 2019  
Page 2 of 25

---

## 1.4. EMERGENCY TELEPHONE NUMBER

24 Hour Emergency Telephone:  
National Poison Control Centre:

(UK) (+44) (0) 23 8089 1558  
(UK) 111 / (IE) (+353)1 809 2166

<b>SECTION 2</b>	<b>HAZARDS IDENTIFICATION</b>
------------------	-------------------------------

## 2.1. CLASSIFICATION OF SUBSTANCE OR MIXTURE

### Classification according to Regulation (EC) No 1272/2008

Aspiration toxicant: Category 1.

H304: May be fatal if swallowed and enters airways.

## 2.2. LABEL ELEMENTS

### Label elements according to Regulation (EC) No 1272/2008

#### Pictograms:



**Signal Word:** Danger

#### Hazard Statements:

H304: May be fatal if swallowed and enters airways.

#### Precautionary Statements:

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents and container in accordance with local regulations.

**Contains:** Distillates (petroleum), solvent-dewaxed heavy paraffinic

## 2.3. OTHER HAZARDS

### Physical / Chemical Hazards:

No significant hazards.

### Health Hazards:

Excessive exposure may result in eye, skin, or respiratory irritation.

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 3 of 25

**Environmental Hazards:**

No significant hazards. Material does not meet the criteria for PBT or vPvB in accordance with REACH Annex XIII.

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

**3.1. SUBSTANCES**

This material is defined as a substance. This SDS covers materials that have different CAS#. The composition is 100% of one of the CAS# in the Reportable Hazardous Substance(s) or Complex Substance(s) table.

**Reportable hazardous substance(s) complying with the classification criteria and/or with an exposure limit (OEL)**

Name	CAS#	EC#	Registration#	Concentration *	GHS/CLP classification
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25	100%	Asp. Tox. 1 H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27	100%	Asp. Tox. 1 H304

Note - any classification in brackets is a GHS building block that was not adopted by the EU in the CLP regulation (No 1272/2008) and therefore is not applicable in the EU or in non-EU countries which have implemented the CLP regulation and is shown for informational purposes only.

Note: See SDS Section 16 for full text of hazard statements.

**3.2. MIXTURES** Not Applicable. This product is regulated as a substance.

**SECTION 4 FIRST AID MEASURES**

**4.1. DESCRIPTION OF FIRST AID MEASURES**

**INHALATION**

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

**SKIN CONTACT**

Wash contact areas with soap and water.

**EYE CONTACT**

Flush thoroughly with water. If irritation occurs, get medical assistance.

**INGESTION**

Seek immediate medical attention. Do not induce vomiting.

Product Name: MOBILTHERM 603  
Revision Date: 12 Dec 2019  
Page 4 of 25

---

#### 4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

No important symptoms or effects.

#### 4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

---

### SECTION 5 FIRE FIGHTING MEASURES

#### 5.1. EXTINGUISHING MEDIA

**Suitable Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Unsuitable Extinguishing Media:** Straight streams of water

#### 5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

**Hazardous Combustion Products:** Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulphur oxides

#### 5.3. ADVICE FOR FIRE FIGHTERS

**Fire Fighting Instructions:** Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

#### FLAMMABILITY PROPERTIES

**Flash Point [Method]:** >194°C (381°F) [ASTM D-92]

**Upper/Lower Flammable Limits (Approximate volume % in air):** UEL: 7.0 LEL: 0.9 [Estimated]

**Autoignition Temperature:** No data available

---

### SECTION 6 ACCIDENTAL RELEASE MEASURES

#### 6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

##### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

##### PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

For emergency responders: Respiratory protection: respiratory protection will be necessary only in special cases, e.g., formation of mists. Half-face or full-face respirator with filter(s) for dust/organic vapor or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to hydrocarbons are

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 5 of 25

recommended. Gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

## 6.2. ENVIRONMENTAL PRECAUTIONS

**Large Spills:** Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

## 6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

**Land Spill:** Stop leak if you can do so without risk. Recover by pumping or with suitable absorbent.

**Water Spill:** Stop leak if you can do so without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

## 6.4. REFERENCES TO OTHER SECTIONS

See Sections 8 and 13.

## SECTION 7

## HANDLING AND STORAGE

### 7.1. PRECAUTIONS FOR SAFE HANDLING

Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or earthing procedures. However, bonding and earthing may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

**Static Accumulator:** This material is a static accumulator.

### 7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

The type of container used to store the material may affect static accumulation and dissipation. Do not store in open or unlabelled containers.

### 7.3. SPECIFIC END USES

Section 1 informs about identified end-uses. No industrial or sector specific guidance available.

## SECTION 8

## EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1. CONTROL PARAMETERS

#### EXPOSURE LIMIT VALUES

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 6 of 25

**Exposure limits/standards (Note: Exposure limits are not additive)**

Substance Name	Form	Limit/Standard			Note	Source
Distillates (petroleum), hydrotreated heavy paraffinic	Inhalable fraction.	TWA	5 mg/m <sup>3</sup>			ACGIH
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Inhalable fraction.	TWA	5 mg/m <sup>3</sup>			ACGIH

**Exposure limits/standards for materials that can be formed when handling this product:** When mists/aerosols can occur the following is recommended: 5 mg/m<sup>3</sup> - ACGIH TLV (inhalable fraction).

Note: Information about recommended monitoring procedures can be obtained from the relevant agency(ies)/institute(s):

UK Health and Safety Executive (HSE)

**DERIVED NO EFFECT LEVEL (DNEL)/DERIVED MINIMAL EFFECT LEVEL (DMEL)**

**Worker**

Substance Name	Dermal	Inhalation
Distillates (petroleum), solvent-dewaxed heavy paraffinic	NA	5.4 mg/m <sup>3</sup> DNEL, Chronic Exposure, Local Effects
Distillates (petroleum), hydrotreated heavy paraffinic	NA	5.4 mg/m <sup>3</sup> DNEL, Chronic Exposure, Local Effects

**Consumer**

Substance Name	Dermal	Inhalation	Oral
Distillates (petroleum), solvent-dewaxed heavy paraffinic	NA	1.2 mg/m <sup>3</sup> DNEL, Chronic Exposure, Local Effects	NA
Distillates (petroleum), hydrotreated heavy paraffinic	NA	1.2 mg/m <sup>3</sup> DNEL, Chronic Exposure, Local Effects	NA

Note: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

**PREDICTED NO EFFECT CONCENTRATION (PNEC)**

Substance Name	Aqua	Aqua	Aqua	Sewage	Sediment	Soil	Oral
----------------	------	------	------	--------	----------	------	------

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 7 of 25

	(fresh water)	(marine water)	(intermittent release)	treatment plant			(secondary poisoning)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	NA	NA	NA	NA	NA	NA	9.33 mg / kg (food)
Distillates (petroleum), hydrotreated heavy paraffinic	NA	NA	NA	NA	NA	NA	9.33 mg / kg (food)

## 8.2. EXPOSURE CONTROLS

### ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

### PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No special requirements under ordinary conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

No protection is ordinarily required under normal conditions of use.

**Eye Protection:** If contact is likely, safety glasses with side shields are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 8 of 25

---

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

**For Summary of Risk Management Measures across all identified uses, see Annex.**

## ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

**Note:** Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

### 9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Liquid  
**Colour:** Pale Yellow  
**Odour:** Characteristic  
**Odour Threshold:** No data available  
**pH:** Not technically feasible  
**Melting Point:** Not technically feasible  
**Freezing Point:** No data available  
**Initial Boiling Point / and Boiling Range:** > 316°C (600°F) [Estimated]  
**Flash Point [Method]:** >194°C (381°F) [ASTM D-92]  
**Evaporation Rate (n-butyl acetate = 1):** No data available  
**Flammability (Solid, Gas):** Not technically feasible  
**Upper/Lower Flammable Limits (Approximate volume % in air):** UEL: 7.0 LEL: 0.9 [Estimated]  
**Vapour Pressure:** < 0.013 kPa (0.1 mm Hg) at 20 °C [Estimated]  
**Vapour Density (Air = 1):** > 2 at 101 kPa [Estimated]  
**Relative Density:** 0.9 [ASTM D1298]  
**Solubility(ies): water** Negligible  
**Partition coefficient (n-Octanol/Water Partition Coefficient):** > 3.5 [Estimated]  
**Autoignition Temperature:** No data available  
**Decomposition Temperature:** No data available  
**Viscosity:** 19.8 cSt (19.8 mm<sup>2</sup>/sec) at 40°C | 4.1 cSt (4.1 mm<sup>2</sup>/sec) at 100°C [ASTM D 445]  
**Explosive Properties:** None  
**Oxidizing Properties:** None

### 9.2. OTHER INFORMATION

**Pour Point:** -18°C (0°F) [ASTM D97]  
**DMSO Extract (mineral oil only), IP-346:** < 3 %wt



Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 9 of 25

<b>SECTION 10</b>	<b>STABILITY AND REACTIVITY</b>
-------------------	---------------------------------

**10.1. REACTIVITY:** See sub-sections below.

**10.2. CHEMICAL STABILITY:** Material is stable under normal conditions.

**10.3. POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.

**10.4. CONDITIONS TO AVOID:** Excessive heat. High energy sources of ignition.

**10.5. INCOMPATIBLE MATERIALS:** Strong oxidisers

**10.6. HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

<b>SECTION 11</b>	<b>TOXICOLOGICAL INFORMATION</b>
-------------------	----------------------------------

**11.1. INFORMATION ON TOXICOLOGICAL EFFECTS**

<b>Hazard Class</b>	<b>Conclusion / Remarks</b>
<b>Inhalation</b>	
Acute Toxicity: (Rat) 4 hour(s) LC50 > 5000 mg/m3 (Aerosol) Test scores or other study results do not meet criteria for classification.	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 403
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
<b>Ingestion</b>	
Acute Toxicity (Rat): LD50 > 5000 mg/kg Test scores or other study results do not meet criteria for classification.	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 401
<b>Skin</b>	
Acute Toxicity (Rabbit): LD50 > 5000 mg/kg Test scores or other study results do not meet criteria for classification.	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 402
Skin Corrosion/Irritation (Rabbit): Data available. Test scores or other study results do not meet criteria for classification.	Negligible irritation to skin at ambient temperatures. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 404
<b>Eye</b>	
Serious Eye Damage/Irritation (Rabbit): Data available. Test scores or other study results do not meet criteria for classification.	May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 405
<b>Sensitisation</b>	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: Data available. Test scores or other study results do not meet criteria for classification.	Not expected to be a skin sensitizer. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 406
<b>Aspiration:</b> Data available.	May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material.
<b>Germ Cell Mutagenicity:</b> Data available. Test scores or other study results do not meet criteria for classification.	Not expected to be a germ cell mutagen. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 471 473 474 476

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 10 of 25

<b>Carcinogenicity:</b> Data available. Test scores or other study results do not meet criteria for classification.	Not expected to cause cancer. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 451 453
<b>Reproductive Toxicity:</b> Data available. Test scores or other study results do not meet criteria for classification.	Not expected to be a reproductive toxicant. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 414 421
<b>Lactation:</b> No end point data for material.	Not expected to cause harm to breast-fed children.
<b>Specific Target Organ Toxicity (STOT)</b>	
Single Exposure: No end point data for material.	Not expected to cause organ damage from a single exposure.
Repeated Exposure: Data available. Test scores or other study results do not meet criteria for classification.	Not expected to cause organ damage from prolonged or repeated exposure. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 408 410 411 412 453

## OTHER INFORMATION

### For the product itself:

Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitising in test animals.

## SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

### 12.1. TOXICITY

Material -- Not expected to be harmful to aquatic organisms.

### 12.2. PERSISTENCE AND DEGRADABILITY

#### Biodegradation:

Material -- Expected to be inherently biodegradable

### 12.3. BIOACCUMULATIVE POTENTIAL

Material -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

### 12.4. MOBILITY IN SOIL

Material -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

Material -- Low potential to migrate through soil.

### 12.5. PERSISTENCE, BIOACCUMULATION AND TOXICITY FOR SUBSTANCE(S)

Material does not meet the Reach Annex XIII criteria for PBT or vPvB.

## 12.6. OTHER ADVERSE EFFECTS

No adverse effects are expected.

## ECOLOGICAL DATA

### Ecotoxicity

Test	Duration	Organism Type	Test Results
Aquatic - Acute Toxicity	48 hour(s)	Daphnia magna	EL0 1000 - 10000 mg/l: data for similar materials
Aquatic - Acute Toxicity	96 hour(s)	Pimephales promelas	LL0 100 mg/l: data for similar materials
Aquatic - Acute Toxicity	72 hour(s)	Pseudokirchneriella subcapitata	EL0 100 mg/l: data for similar materials
Aquatic - Chronic Toxicity	21 day(s)	Daphnia magna	NOELR 10 - 1000 mg/l: data for similar materials
Aquatic - Chronic Toxicity	72 hour(s)	Pseudokirchneriella subcapitata	NOELR 100 mg/l: data for similar materials

### Persistence, Degradability and Bioaccumulation Potential

Media	Test Type	Duration	Test Results: Basis
Water	Ready Biodegradability	28 day(s)	Percent Degraded < 60 : similar material

## SECTION 13 DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

### 13.1. WASTE TREATMENT METHODS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Protect the environment. Dispose of used oil at designated sites. Minimize skin contact. Do not mix used oils with solvents, brake fluids or coolants.

**European Waste Code:** 13 03 07\*

NOTE: These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste disposal code(s).

This material is considered as hazardous waste pursuant to Directive 91/689/EEC on hazardous waste, and subject to the provisions of that Directive unless Article 1(5) of that Directive applies.

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 12 of 25

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

<b>SECTION 14</b>	<b>TRANSPORT INFORMATION</b>
-------------------	------------------------------

**LAND (ADR/RID):** 14.1-14.6 Not Regulated for Land Transport

**INLAND WATERWAYS (ADN):** 14.1-14.6 Not Regulated for Inland Waterways Transport

**SEA (IMDG):** 14.1-14.6 Not Regulated for Sea Transport according to IMDG-Code

**SEA (MARPOL 73/78 Convention - Annex II):**

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code  
Not classified according to Annex II

**AIR (IATA):** 14.1-14.6 Not Regulated for Air Transport

<b>SECTION 15</b>	<b>REGULATORY INFORMATION</b>
-------------------	-------------------------------

**REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS**

Listed or exempt from listing/notification on the following chemical inventories (May contain substance(s) subject to notification to the EPA Active TSCA inventory prior to import to USA): AICS, DSL, ENCS, IECSC, KECI, PICCS, TSCA

**15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE****Applicable EU Directives and Regulations:**

1907/2006 [... on the Registration, Evaluation, Authorisation and Restriction of Chemicals ... and amendments thereto]

1272/2008 [on classification, labelling and packaging of substances and mixtures.. and amendments thereto]

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 13 of 25

## 15.2. CHEMICAL SAFETY ASSESSMENT

**REACH Information:** A Chemical Safety Assessment has been carried out for one or more substances present in the material.

<b>SECTION 16</b>	<b>OTHER INFORMATION</b>
-------------------	--------------------------

### IDENTIFIED USES:

Lubricants - Industrial (PROC1, PROC10, PROC13, PROC17, PROC18, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, SU3)

Lubricants - Professional (Low Release) (PROC1, PROC10, PROC11, PROC13, PROC17, PROC18, PROC2, PROC20, PROC3, PROC4, PROC8a, PROC8b, PROC9, SU22)

Lubricants - Professional (High Release) (PROC1, PROC10, PROC11, PROC13, PROC17, PROC18, PROC2, PROC20, PROC3, PROC4, PROC8a, PROC8b, PROC9, SU22)

Lubricants - Consumer (Low Release) (PC01, PC24, PC31, SU21)

Lubricants - Consumer (High Release) (PC01, PC24, PC31, SU21)

**REFERENCES:** Sources of information used in preparing this SDS included one or more of the following: results from in house or supplier toxicology studies, CONCAWE Product Dossiers, publications from other trade associations, such as the EU Hydrocarbon Solvents REACH Consortium, U.S. HPV Program Robust Summaries, the EU IUCLID Data Base, U.S. NTP publications, and other sources, as appropriate.

### List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

Acronym	Full text
N/A	Not applicable
N/D	Not determined
NE	Not established
VOC	Volatile Organic Compound
AICS	Australian Inventory of Chemical Substances
AIHA WEEL	American Industrial Hygiene Association Workplace Environmental Exposure Limits
ASTM	ASTM International, originally known as the American Society for Testing and Materials (ASTM)
DSL	Domestic Substance List (Canada)
EINECS	European Inventory of Existing Commercial Substances
ELINCS	European List of Notified Chemical Substances
ENCS	Existing and new Chemical Substances (Japanese inventory)
IECSC	Inventory of Existing Chemical Substances in China
KECI	Korean Existing Chemicals Inventory
NDSL	Non-Domestic Substances List (Canada)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances
TLV	Threshold Limit Value (American Conference of Governmental Industrial Hygienists)
TSCA	Toxic Substances Control Act (U.S. inventory)
UVCB	Substances of Unknown or Variable composition, Complex reaction products or Biological materials
LC	Lethal Concentration
LD	Lethal Dose
LL	Lethal Loading
EC	Effective Concentration

Product Name: MOBILTHERM 603  
 Revision Date: 12 Dec 2019  
 Page 14 of 25

EL Effective Loading  
 NOEC No Observable Effect Concentration  
 NOELR No Observable Effect Loading Rate

**KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):**  
 Asp. Tox. 1 H304: May be fatal if swallowed and enters airways; Aspiration, Cat 1

**THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**  
 No revision information

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

Internal Use Only  
 MHC: 2A, 0B, 0, 0, 0, 0 PPEC: A  
 DGN: 2011270QGB (548419)

**ANNEX**

<b>Section 1 Exposure Scenario Title</b>	
<b>Title:</b>	
Lubricants - Industrial	
<b>Use Descriptor</b>	
Sector(s) of Use	SU3
Process Categories	PROC1, PROC10, PROC13, PROC17, PROC18, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9
Environmental Release Categories	ERC4, ERC7
Specific Environmental Release Category	
<b>Processes, tasks, activities covered</b>	
Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of machinery/engines and similar articles, reworking on reject articles, equipment maintenance and disposal of wastes.	

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 15 of 25

<b>Section 2 Operational conditions and risk management measures</b>
<b>Section 2.1 Control of worker exposure</b>
<b>Product Characteristic</b>
Liquid
<b>Duration, frequency and amount</b>
Covers daily exposures up to 8 hours (unless stated differently)[G2] Covers percentage substance in the product up to 100 %[G13 ]
<b>Other given operational conditions affecting workers exposure</b>
Assumes a good basic standard of occupational hygiene is implemented [G1]
<b>Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions</b> (only required controls to demonstrate safe use listed)
<b>General measures (Aspiration Hazard)</b> The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting.
<b>Section 2.2 Control of environmental exposure</b>
<b>Product characteristics</b>
Not applicable
<b>Duration, frequency and amount</b>
Not applicable
<b>Environmental factors not influenced by risk management</b>
Not applicable
<b>Other given operational conditions affecting environmental exposure</b>
Not applicable
<b>Technical conditions and measures at process level (source) to prevent release</b>
Not applicable
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>
Not applicable
<b>Organisation measures to prevent/limit release from site</b>
Not applicable
<b>Conditions and measures related to municipal sewage treatment plant</b>
Not applicable
Conditions and measures related to external treatment of waste for disposal
Not applicable
Conditions and measures related to external recovery of waste
Not applicable
<b>Section 3 Exposure Estimation</b>
<b>3.1. Health</b>
Not applicable
<b>3.2. Environment</b>
Not applicable
<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>
<b>4.1. Health</b>
Available hazard data do not support the need for a DNEL to be established for other health effects.[G36] Risk Management Measures are based on qualitative risk characterisation. [G37]
<b>4.2. Environment</b>

Product Name: MOBILTHERM 603  
Revision Date: 12 Dec 2019  
Page 16 of 25

Not applicable
----------------



<b>Section 1 Exposure Scenario Title</b>	
<b>Title:</b>	
Lubricants - Professional (Low Release)	
<b>Use Descriptor</b>	
Sector(s) of Use	SU22
Process Categories	PROC1, PROC10, PROC11, PROC13, PROC17, PROC18, PROC2, PROC20, PROC3, PROC4, PROC8a, PROC8b, PROC9
Environmental Release Categories	ERC9A, ERC9B
Specific Environmental Release Category	
<b>Processes, tasks, activities covered</b>	
Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>Section 2.1 Control of worker exposure</b>	
<b>Product Characteristic</b>	
Liquid	
<b>Duration, frequency and amount</b>	
Covers daily exposures up to 8 hours (unless stated differently)[G2] Covers percentage substance in the product up to 100 %[G13]	
<b>Other given operational conditions affecting workers exposure</b>	
Assumes a good basic standard of occupational hygiene is implemented [G1]	
<b>Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions (only required controls to demonstrate safe use listed)</b>	
<b>General measures (Aspiration Hazard)</b>	
The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting.	
<b>Section 2.2 Control of environmental exposure</b>	
<b>Product characteristics</b>	
Not applicable	
<b>Duration, frequency and amount</b>	
Not applicable	
<b>Environmental factors not influenced by risk management</b>	
Not applicable	
<b>Other given operational conditions affecting environmental exposure</b>	
Not applicable	
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Not applicable	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Not applicable	
<b>Organisation measures to prevent/limit release from site</b>	
Not applicable	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Not applicable	

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 18 of 25

Conditions and measures related to external treatment of waste for disposal
Not applicable
Conditions and measures related to external recovery of waste
Not applicable
<b>Section 3 Exposure Estimation</b>
<b>3.1. Health</b>
Not applicable
<b>3.2. Environment</b>
Not applicable
<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>
<b>4.1. Health</b>
Available hazard data do not support the need for a DNEL to be established for other health effects.[G36] Risk Management Measures are based on qualitative risk characterisation. [G37]
<b>4.2. Environment</b>
Not applicable

Product Name: MOBILTHERM 603  
 Revision Date: 12 Dec 2019  
 Page 19 of 25

<b>Section 1 Exposure Scenario Title</b>	
<b>Title:</b>	
Lubricants - Professional (High Release)	
<b>Use Descriptor</b>	
Sector(s) of Use	SU22
Process Categories	PROC1, PROC10, PROC11, PROC13, PROC17, PROC18, PROC2, PROC20, PROC3, PROC4, PROC8a, PROC8b, PROC9
Environmental Release Categories	ERC8A, ERC8D
Specific Environmental Release Category	
<b>Processes, tasks, activities covered</b>	
Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>Section 2.1 Control of worker exposure</b>	
<b>Product Characteristic</b>	
Liquid	
<b>Duration, frequency and amount</b>	
Covers daily exposures up to 8 hours (unless stated differently)[G2] Covers percentage substance in the product up to 100 %[G13]	
<b>Other given operational conditions affecting workers exposure</b>	
Assumes a good basic standard of occupational hygiene is implemented [G1]	
<b>Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions (only required controls to demonstrate safe use listed)</b>	
<b>General measures (Aspiration Hazard)</b>	
The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting.	
<b>Section 2.2 Control of environmental exposure</b>	
<b>Product characteristics</b>	
Not applicable	
<b>Duration, frequency and amount</b>	
Not applicable	
<b>Environmental factors not influenced by risk management</b>	
Not applicable	
<b>Other given operational conditions affecting environmental exposure</b>	
Not applicable	
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Not applicable	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Not applicable	
<b>Organisation measures to prevent/limit release from site</b>	
Not applicable	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Not applicable	

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 20 of 25

Conditions and measures related to external treatment of waste for disposal
Not applicable
Conditions and measures related to external recovery of waste
Not applicable
<b>Section 3 Exposure Estimation</b>
<b>3.1. Health</b>
Not applicable
<b>3.2. Environment</b>
Not applicable
<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>
<b>4.1. Health</b>
Available hazard data do not support the need for a DNEL to be established for other health effects.[G36] Risk Management Measures are based on qualitative risk characterisation. [G37]
<b>4.2. Environment</b>
Not applicable

<b>Section 1 Exposure Scenario Title</b>	
<b>Title:</b>	
Lubricants - Consumer (Low Release)	
<b>Use Descriptor</b>	
Sector(s) of Use	SU21
Product Categories	PC01, PC24, PC31
Environmental Release Categories	ERC9A, ERC9B
Specific Environmental Release Category	
<b>Processes, tasks, activities covered</b>	
Covers the consumer use of formulated lubricants in closed and open systems including transfer operations, application, operation of engines and similar articles, equipment maintenance and disposal of waste oil.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>Section 2.1 Control of consumer exposure</b>	
<b>Product Characteristic</b>	
Liquid	
<b>Duration, frequency and amount</b>	
Not applicable	
<b>Other given operational conditions affecting consumer exposure</b>	
General measures (Aspiration Hazard) The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting. Just a sip of lamp oil - or even sucking the wick of lamps may lead to life threatening lung damage. Keep lamps filled with this liquid out of the reach of children.	
<b>Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions</b> (only required controls to demonstrate safe use listed)	
<b>Section 2.2 Control of environmental exposure</b>	
<b>Product characteristics</b>	
Not applicable	
<b>Duration, frequency and amount</b>	
Not applicable	
<b>Environmental factors not influenced by risk management</b>	
Not applicable	
<b>Other given operational conditions affecting environmental exposure</b>	
Not applicable	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Not applicable	
Conditions and measures related to external treatment of waste for disposal	
Not applicable	
Conditions and measures related to external recovery of waste	
Not applicable	
<b>Section 3 Exposure Estimation</b>	
<b>3.1. Health</b>	
Not applicable	

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 22 of 25

<b>3.2. Environment</b>
Not applicable
<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>
<b>4.1. Health</b>
Available hazard data do not support the need for a DNEL to be established for other health effects.[G36] Risk Management Measures are based on qualitative risk characterisation. [G37]
<b>4.2. Environment</b>
Not applicable

Product Name: MOBILTHERM 603  
 Revision Date: 12 Dec 2019  
 Page 23 of 25

<b>Section 1 Exposure Scenario Title</b>	
<b>Title:</b>	
Lubricants - Consumer (High Release)	
<b>Use Descriptor</b>	
Sector(s) of Use	SU21
Product Categories	PC01, PC24, PC31
Environmental Release Categories	ERC8A, ERC8D
Specific Environmental Release Category	
<b>Processes, tasks, activities covered</b>	
Covers the consumer use of formulated lubricants in closed and open systems including transfer operations, application, operation of engines and similar articles, equipment maintenance and disposal of waste oil.	
<b>Section 2 Operational conditions and risk management measures</b>	
<b>Section 2.1 Control of consumer exposure</b>	
<b>Product Characteristic</b>	
Liquid	
<b>Duration, frequency and amount</b>	
Not applicable	
<b>Other given operational conditions affecting consumer exposure</b>	
General measures (Aspiration Hazard) The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting. Just a sip of lamp oil - or even sucking the wick of lamps may lead to life threatening lung damage. Keep lamps filled with this liquid out of the reach of children.	
<b>Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions</b> (only required controls to demonstrate safe use listed)	
<b>Section 2.2 Control of environmental exposure</b>	
<b>Product characteristics</b>	
Not applicable	
<b>Duration, frequency and amount</b>	
Not applicable	
<b>Environmental factors not influenced by risk management</b>	
Not applicable	
<b>Other given operational conditions affecting environmental exposure</b>	
Not applicable	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Not applicable	
Conditions and measures related to external treatment of waste for disposal	
Not applicable	
Conditions and measures related to external recovery of waste	
Not applicable	
<b>Section 3 Exposure Estimation</b>	
<b>3.1. Health</b>	
Not applicable	
<b>3.2. Environment</b>	

Product Name: MOBILTHERM 603

Revision Date: 12 Dec 2019

Page 24 of 25

Not applicable
<b>Section 4 Guidance to check compliance with the Exposure Scenario</b>
<b>4.1. Health</b>
Available hazard data do not support the need for a DNEL to be established for other health effects.[G36] Risk Management Measures are based on qualitative risk characterisation. [G37]
<b>4.2. Environment</b>
Not applicable



Product Name: MOBILTHERM 603  
Revision Date: 12 Dec 2019  
Page 25 of 25

---