

SAFETY DATA SHEET

| | |
|------------------|-----------------------------------------------------------------------------------|
| SECTION 1 | IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING |
|------------------|-----------------------------------------------------------------------------------|

As of the revision date above, this SDS meets the regulations in the United Kingdom & Ireland.

1.1. PRODUCT IDENTIFIER

Product Name: MOBIL SYSTEM CLEANER
Product Description: Base Oil and Additives
Product Code: 201560B0B710

1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Intended Use: Additive, Cleaning agent

Uses advised against: This product is not recommended for any industrial, professional or consumer use other than the Identified Uses above.

1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Supplier: SOL BARBADOS LIMITED
Spring Garden Highway
St. Michael BB12051
Barbados

Supplier General Contact: 1-246-233-0711, 1-246-467-4741

1.4. EMERGENCY TELEPHONE NUMBER

24 Hour Emergency Telephone: +1 703-741-5970 (CHEMTREC)
National Poison Control Centre: (UK) 111 / (IE) (+353)1 809 2166

| | |
|------------------|-------------------------------|
| SECTION 2 | HAZARDS IDENTIFICATION |
|------------------|-------------------------------|

2.1. CLASSIFICATION OF SUBSTANCE OR MIXTURE

Classification according to Regulation (EC) No 1272/2008

Acute oral toxicant: Category 4. Skin irritation: Category 2. Serious eye damage: Category 1. Skin Sensitizer: Category 1.

Acute aquatic toxicant: Category 1. Chronic aquatic toxicant: Category 1.

Product Name: MOBIL SYSTEM CLEANER

Revision Date: 12 Dec 2019

Page 2 of 14

H302: Harmful if swallowed. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H318: Causes serious eye damage.
H400: Very toxic to aquatic life. H410: Very toxic to aquatic life with long lasting effects.

2.2. LABEL ELEMENTS

Label elements according to Regulation (EC) No 1272/2008

Pictograms:



Signal Word: Danger

Hazard Statements:

H302: Harmful if swallowed. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H318: Causes serious eye damage.
H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statements:

P261: Avoid breathing mist / vapours. P264: Wash skin thoroughly after handling. P270: Do not eat, drink or smoke when using this product. P272: Contaminated work clothing should not be allowed out of the workplace. P273: Avoid release to the environment. P280: Wear protective gloves and eye / face protection.
P301 + P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER/doctor/physician. P330: Rinse mouth. P333 + P313: If skin irritation or rash occurs: Get medical advice/attention. P362 + P364: Take off contaminated clothing and wash it before reuse. P391: Collect spillage.
P501: Dispose of contents and container in accordance with local regulations.

Contains: ETHOXYLATED ALCOHOLS; PROPOXYLATED DIAMINE

2.3. OTHER HAZARDS

Physical / Chemical Hazards:

No significant hazards.

Health Hazards:

High-pressure injection under skin may cause serious damage. May be irritating to nose, throat, and lungs.

Environmental Hazards:

Product Name: MOBIL SYSTEM CLEANER

Revision Date: 12 Dec 2019

Page 3 of 14

No additional hazards. Material does not meet the criteria for PBT or vPvB in accordance with REACH Annex XIII.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1. SUBSTANCES Not Applicable. This material is regulated as a mixture.

3.2. MIXTURES

This material is defined as a mixture.

Reportable hazardous substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

| Name | CAS# | EC# | Registration# | Concentration * | GHS/CLP classification |
|-----------------------------------------------------------|------------|-----------|---------------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| ALCOHOLS, C9-11, ETHOXYLATED | 68439-46-3 | | NE | 10 - < 20% | [Aquatic Acute 2 H401], Acute Tox. 4 H302, Eye Dam. 1 H318 |
| AMINES, N-TALLOW ALKYLTRIMETHYLENEDI-, PROPOXYLATED | 68603-75-8 | | NE | 10 - < 20% | Acute Tox. 4 H302, Skin Sens. 1 H317, Aquatic Acute 1 H400 (M factor 10), Aquatic Chronic 1 H410 (M factor 10), Skin Corr. 1B H314 |
| SULFONIC ACIDS, PETROLEUM, CALCIUM SALTS | 61789-86-4 | 263-093-9 | NE | 5 - < 10% | Eye Irrit. 2 H319 |

Note - any classification in brackets is a GHS building block that was not adopted by the EU in the CLP regulation (No 1272/2008) and therefore is not applicable in the EU or in non-EU countries which have implemented the CLP regulation and is shown for informational purposes only.

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Note: See SDS Section 16 for full text of hazard statements.

SECTION 4 FIRST AID MEASURES

4.1. DESCRIPTION OF FIRST AID MEASURES

INHALATION

Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device.

SKIN CONTACT

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a

Product Name: MOBIL SYSTEM CLEANER

Revision Date: 12 Dec 2019

Page 4 of 14

surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

INGESTION

Give one or two glasses of water if patient is alert and able to swallow. Seek immediate medical attention. Do not induce vomiting.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye pain, redness, tearing, swelling of eyelids, itching. Itching, pain, redness, swelling of skin. Local necrosis as evidenced by delayed onset of pain and tissue damage a few hours after injection. Itching and rash from allergic skin reaction.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

The need to have special means for providing specific and immediate medical treatment available in the workplace is not expected.

SECTION 5 FIRE FIGHTING MEASURES

5.1. EXTINGUISHING MEDIA

Suitable Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Unsuitable Extinguishing Media: Straight streams of water

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Hazardous Combustion Products: Aldehydes, Incomplete combustion products, Nitrogen oxides, Oxides of carbon, Smoke, Fume, Sulphur oxides

5.3. ADVICE FOR FIRE FIGHTERS

Fire Fighting Instructions: Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Unusual Fire Hazards: Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

FLAMMABILITY PROPERTIES

Flash Point [Method]: >93°C (200°F) [ASTM D-93]

Upper/Lower Flammable Limits (Approximate volume % in air): UEL: No data available LEL: No data available

Autoignition Temperature: No data available

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

For emergency responders: Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

6.2. ENVIRONMENTAL PRECAUTIONS

Large Spills: Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Land Spill: Stop leak if you can do so without risk. Do not touch or walk through spilled material. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. **Small Spills:** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. If liquid is too viscous for pumping, shovel it up into a suitable container for recycle or disposal.

Water Spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

6.4. REFERENCES TO OTHER SECTIONS

See Sections 8 and 13.

| |
|------------------|
| SECTION 7 |
|------------------|

| |
|-----------------------------|
| HANDLING AND STORAGE |
|-----------------------------|

7.1. PRECAUTIONS FOR SAFE HANDLING

Avoid contact with skin. Avoid contact with eyes. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or earthing procedures. However, bonding and earthing may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

Product Name: MOBIL SYSTEM CLEANER

Revision Date: 12 Dec 2019

Page 6 of 14

Static Accumulator: This material is a static accumulator.

7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

The type of container used to store the material may affect static accumulation and dissipation. Do not store in open or unlabelled containers. Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well-ventilated area.

7.3. SPECIFIC END USES

Section 1 informs about identified end-uses. No industrial or sector specific guidance available.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. CONTROL PARAMETERS

Exposure limits/standards for materials that can be formed when handling this product: When mists/aerosols can occur the following is recommended: 5 mg/m³ - ACGIH TLV (inhalable fraction).

Note: Information about recommended monitoring procedures can be obtained from the relevant agency(ies)/institute(s):

UK Health and Safety Executive (HSE)

8.2. EXPOSURE CONTROLS

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Adequate ventilation should be provided so that exposure limits are not exceeded. Eye washes and showers for emergency use.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Product Name: MOBIL SYSTEM CLEANER

Revision Date: 12 Dec 2019

Page 7 of 14

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

Full face filter respirator

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended. Nitrile, minimum 0.38 mm thickness or comparable protective barrier material with a high performance level for continuous contact use conditions, permeation breakthrough minimum 480 minutes in accordance with CEN standards EN 420 and EN 374.

Eye Protection: Chemical goggles and face shield are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

Chemical/oil resistant clothing is recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Form: Viscous

Colour: Brown

Product Name: MOBIL SYSTEM CLEANER

Revision Date: 12 Dec 2019

Page 8 of 14

Odour: Ammonia-like

Odour Threshold: No data available

pH: Not technically feasible

Melting Point: Not technically feasible

Freezing Point: No data available

Initial Boiling Point / and Boiling Range: No data available

Flash Point [Method]: >93°C (200°F) [ASTM D-93]

Evaporation Rate (n-butyl acetate = 1): No data available

Flammability (Solid, Gas): Not technically feasible

Upper/Lower Flammable Limits (Approximate volume % in air): UEL: No data available LEL: No data available

Vapour Pressure: [N/D at 20°C] [test method unavailable]

Vapour Density (Air = 1): No data available

Relative Density (at 15 °C): 0.92 [test method unavailable]

Solubility(ies): water Appreciable

Partition coefficient (n-Octanol/Water Partition Coefficient): No data available

Autoignition Temperature: No data available

Decomposition Temperature: No data available

Viscosity: 55 cSt (55 mm²/sec) at 40°C [test method unavailable]

Explosive Properties: No data available

Oxidizing Properties: None

9.2. OTHER INFORMATION

DMSO Extract (mineral oil only), IP-346: < 3 %wt

| | |
|-------------------|---------------------------------|
| SECTION 10 | STABILITY AND REACTIVITY |
|-------------------|---------------------------------|

10.1. REACTIVITY: See sub-sections below.

10.2. CHEMICAL STABILITY: Material is stable under normal conditions.

10.3. POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization will not occur.

10.4. CONDITIONS TO AVOID: Excessive heat. High energy sources of ignition.

10.5. INCOMPATIBLE MATERIALS: Strong Acids, Strong oxidisers

10.6. HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

| | |
|-------------------|----------------------------------|
| SECTION 11 | TOXICOLOGICAL INFORMATION |
|-------------------|----------------------------------|

11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

| <u>Hazard Class</u> | <u>Conclusion / Remarks</u> |
|-------------------------------------------------|---------------------------------------------------------|
| Inhalation | |
| Acute Toxicity: No end point data for material. | Minimally Toxic. Based on assessment of the components. |

Product Name: MOBIL SYSTEM CLEANER

Revision Date: 12 Dec 2019

Page 9 of 14

| | |
|----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Irritation: No end point data for material. | Elevated temperatures or mechanical action may form vapours, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs. |
| Ingestion | |
| Acute Toxicity: No end point data for material. | Minimally Toxic. Based on assessment of the components. |
| Skin | |
| Acute Toxicity: No end point data for material. | Minimally Toxic. Based on assessment of the components. |
| Skin Corrosion/Irritation: No end point data for material. | Irritating to the skin. Based on assessment of the components. |
| Eye | |
| Serious Eye Damage/Irritation: No end point data for material. | Severely irritating, and may seriously damage eye tissue. Based on assessment of the components. |
| Sensitisation | |
| Respiratory Sensitization: No end point data for material. | Not expected to be a respiratory sensitizer. |
| Skin Sensitization: No end point data for material. | May cause allergic skin reaction. Based on assessment of the components. |
| Aspiration: Data available. | Not expected to be an aspiration hazard. Based on physico-chemical properties of the material. |
| Germ Cell Mutagenicity: No end point data for material. | Not expected to be a germ cell mutagen. Based on assessment of the components. |
| Carcinogenicity: No end point data for material. | Not expected to cause cancer. Based on assessment of the components. |
| Reproductive Toxicity: No end point data for material. | Not expected to be a reproductive toxicant. Based on assessment of the components. |
| Lactation: No end point data for material. | Not expected to cause harm to breast-fed children. |
| Specific Target Organ Toxicity (STOT) | |
| Single Exposure: No end point data for material. | Not expected to cause organ damage from a single exposure. |
| Repeated Exposure: No end point data for material. | Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components. |

TOXICITY FOR SUBSTANCES

| NAME | ACUTE TOXICITY |
|------------------------------------------------------------|----------------------------------|
| ALCOHOLS, C9-11, ETHOXYLATED | Oral Lethality: 1400 mg/kg (Rat) |
| AMINES, N-TALLOW ALKYLTRIMETHYLENE DI-, PROPOXYLATED | Oral Lethality: 1255 mg/kg (Rat) |

OTHER INFORMATION

For the product itself:

An ingredient or ingredients that are classified as a skin sensitizer.

Contains:

Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitising in test animals.

| | |
|-------------------|-------------------------------|
| SECTION 12 | ECOLOGICAL INFORMATION |
|-------------------|-------------------------------|

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

12.1. TOXICITY

Material -- Expected to be very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

12.2. PERSISTENCE AND DEGRADABILITY Not determined.

12.3. BIOACCUMULATIVE POTENTIAL Not determined.

12.4. MOBILITY IN SOIL

Not determined.

12.5. PERSISTENCE, BIOACCUMULATION AND TOXICITY FOR SUBSTANCE(S)

Material does not meet the Reach Annex XIII criteria for PBT or vPvB.

12.6. OTHER ADVERSE EFFECTS

No adverse effects are expected.

| | |
|-------------------|--------------------------------|
| SECTION 13 | DISPOSAL CONSIDERATIONS |
|-------------------|--------------------------------|

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

13.1. WASTE TREATMENT METHODS

Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

European Waste Code: 13 02 08*

NOTE: These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste disposal code(s).

This material is considered as hazardous waste pursuant to Directive 91/689/EEC on hazardous waste, and subject to the provisions of that Directive unless Article 1(5) of that Directive applies.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should

Product Name: MOBIL SYSTEM CLEANER

Revision Date: 12 Dec 2019

Page 11 of 14

be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14 TRANSPORT INFORMATION

LAND (ADR/RID)

14.1. UN Number: 3082

14.2. UN Proper Shipping Name (Technical Name): ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propoxylated diamine)

14.3. Transport Hazard Class(es): 9

14.4. Packing Group: III

14.5. Environmental Hazards: Yes

14.6. Special Precautions for users:

Classification Code: M6

Label(s) / Mark(s): 9, EHS

Hazard ID Number: 90

Hazchem EAC: 3Z

INLAND WATERWAYS (ADN)

14.1. UN (or ID) Number: 3082

14.2. UN Proper Shipping Name (Technical Name): ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propoxylated diamine)

14.3. Transport Hazard Class(es): 9

14.4. Packing Group: III

14.5. Environmental Hazards: Yes

14.6. Special Precautions for users:

Hazard ID Number: 90

Label(s) / Mark(s): 9, EHS

SEA (IMDG)

14.1. UN Number: 3082

14.2. UN Proper Shipping Name (Technical Name): ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propoxylated diamine)

14.3. Transport Hazard Class(es): 9

14.4. Packing Group: III

14.5. Environmental Hazards: Marine Pollutant

14.6. Special Precautions for users:

Label(s): 9

EMS Number: F-A, S-F

Transport Document Name: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propoxylated diamine), 9, PG III, MARINE POLLUTANT

Footnote: Not subject to the provisions of UN3082 Environmentally hazardous substances liquid, n.o.s., if shipped in quantities of 5 liters or less per single or inner combination packaging as per IMDG code 2.10.2.7.

SEA (MARPOL 73/78 Convention - Annex II):

Product Name: MOBIL SYSTEM CLEANER

Revision Date: 12 Dec 2019

Page 12 of 14

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not classified according to Annex II

AIR (IATA)

14.1. UN Number: 3082

14.2. UN Proper Shipping Name (Technical Name): ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propoxylated diamine)

14.3. Transport Hazard Class(es): 9

14.4. Packing Group: III

14.5. Environmental Hazards: Yes

14.6. Special Precautions for users:

Label(s) / Mark(s): 9, EHS

Transport Document Name: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (Propoxylated diamine), 9, PG III

[Footnote: Not subject to the provisions of UN3082 Environmentally hazardous substances liquid, n.o.s., if shipped in quantities of 5 liters or less per single or inner combination packaging as per Special Provision A197.]

SECTION 15**REGULATORY INFORMATION****REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS**

Listed or exempt from listing/notification on the following chemical inventories (May contain substance(s) subject to notification to the EPA Active TSCA inventory prior to import to USA): AICS, DSL, IECSC, TCSI, TSCA

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE**Applicable EU Directives and Regulations:**

1907/2006 [... on the Registration, Evaluation, Authorisation and Restriction of Chemicals ... and amendments thereto]

96/82/EC as extended by 2003/105/EC [... on the control of major-accident hazards involving dangerous substances]. Product contains a substance that falls within the criteria defined in Annex I. Refer to Directive for details of requirements taking into account the volume of product stored on site.

98/24/EC [... on the protection of workers from the risk related to chemical agents at work ...]. Refer to Directive for details of requirements.

1272/2008 [on classification, labelling and packaging of substances and mixtures.. and amendments thereto]

15.2. CHEMICAL SAFETY ASSESSMENT

Product Name: MOBIL SYSTEM CLEANER

Revision Date: 12 Dec 2019

Page 13 of 14

REACH Information: A Chemical Safety Assessment has been carried out for one or more substances present in the material.

| | |
|-------------------|--------------------------|
| SECTION 16 | OTHER INFORMATION |
|-------------------|--------------------------|

REFERENCES: Sources of information used in preparing this SDS included one or more of the following: results from in house or supplier toxicology studies, CONCAWE Product Dossiers, publications from other trade associations, such as the EU Hydrocarbon Solvents REACH Consortium, U.S. HPV Program Robust Summaries, the EU IUCLID Data Base, U.S. NTP publications, and other sources, as appropriate.

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

| Acronym | Full text |
|-----------|--------------------------------------------------------------------------------------------------|
| N/A | Not applicable |
| N/D | Not determined |
| NE | Not established |
| VOC | Volatile Organic Compound |
| AICS | Australian Inventory of Chemical Substances |
| AIHA WEEL | American Industrial Hygiene Association Workplace Environmental Exposure Limits |
| ASTM | ASTM International, originally known as the American Society for Testing and Materials (ASTM) |
| DSL | Domestic Substance List (Canada) |
| EINECS | European Inventory of Existing Commercial Substances |
| ELINCS | European List of Notified Chemical Substances |
| ENCS | Existing and new Chemical Substances (Japanese inventory) |
| IECSC | Inventory of Existing Chemical Substances in China |
| KECI | Korean Existing Chemicals Inventory |
| NDSL | Non-Domestic Substances List (Canada) |
| NZIoC | New Zealand Inventory of Chemicals |
| PICCS | Philippine Inventory of Chemicals and Chemical Substances |
| TLV | Threshold Limit Value (American Conference of Governmental Industrial Hygienists) |
| TSCA | Toxic Substances Control Act (U.S. inventory) |
| UVCB | Substances of Unknown or Variable composition, Complex reaction products or Biological materials |
| LC | Lethal Concentration |
| LD | Lethal Dose |
| LL | Lethal Loading |
| EC | Effective Concentration |
| EL | Effective Loading |
| NOEC | No Observable Effect Concentration |
| NOELR | No Observable Effect Loading Rate |

Classification according to Regulation (EC) No 1272/2008

| Classification according to Regulation (EC) No 1272/2008 | Classification procedure |
|----------------------------------------------------------|--------------------------|
| Acute Tox. 4; H302 | Calculation |
| Aquatic Acute 1; H400 | Calculation |
| Aquatic Chronic 1; H410 | Calculation |
| Eye Dam. 1; H318 | Calculation |
| Skin Irrit. 2; H315 | Calculation |
| Skin Sens. 1; H317 | Calculation |

Product Name: MOBIL SYSTEM CLEANER

Revision Date: 12 Dec 2019

Page 14 of 14

KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

Acute Tox. 4 H302: Harmful if swallowed; Acute Tox Oral, Cat 4

Skin Corr. 1B H314: Causes severe skin burns and eye damage; Skin Corr/Irritation, Cat 1B

Skin Sens. 1 H317: May cause allergic skin reaction; Skin Sensitization, Cat 1

Eye Dam. 1 H318: Causes serious eye damage; Serious Eye Damage/Irr, Cat 1

Eye Irrit. 2 H319: Causes serious eye irritation; Serious Eye Damage/Irr, Cat 2

Aquatic Acute 1 H400: Very toxic to aquatic life; Acute Env Tox, Cat 1

[Aquatic Acute 2 H401]: Toxic to aquatic life; Acute Env Tox, Cat 2

Aquatic Chronic 1 H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Annex not required information was added.

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

Internal Use Only

MHC: 0, 0, 0, 4, 4, 1

PPEC: E

DGN: 7082067XBB (556290)

| |
|--------------|
| ANNEX |
|--------------|

Annex not required for this material.