

# SAFETY DATA SHEET

# **SECTION 1**

**PRODUCT AND COMPANY IDENTIFICATION** 

# PRODUCT

Product Name: NYVAC FR 200D Product Description: Water-glycol Product Code: 201560108020 Intended Use: Fire-resistant hydraulic fluid

COMPANY IDENTIFICATION

Supplier:

SOL EC LTD (DOMINICA) Fond Cole Roseau Commonwealth of Dominica 24 Hour Health Emergency +1 703-741-5970 (CHEMTREC) **Supplier General Contact** 1-767-255-6178, 1-767-448-3865

# **SECTION 2**

# HAZARDS IDENTIFICATION

This material is hazardous according to regulatory guidelines (see (M)SDS Section 15).

# **CLASSIFICATION:**

Acute oral toxicant: Category 4. Reproductive toxicant (developmental): Category 2. Reproductive toxicant (fertility): Category 2.

LABEL: Pictogram:



Signal Word: Warning

# Hazard Statements:

H302: Harmful if swallowed. H361: Suspected of damaging the unborn child. H361: Suspected of damaging fertility.

# **Precautionary Statements:**

P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use.P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P264: Wash skin thoroughly after handling. P270: Do not eat, drink or smoke when using this product. P280: Wear protective gloves and clothing.P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P315: Get immediate medical advice/attention. P330: Rinse mouth.P405: Store locked up.P501: Dispose of contents and container in accordance with local regulations.



Product Name: NYVAC FR 200D Revision Date: 25 Mar 2022 Page 2 of 11

# Contains: DIETHYLENE GLYCOL; MORPHOLINE; SODIUM 4 (OR 5) -METHYL-1H-BENZOTRIAZOLE

# Other hazard information:

# HAZARD NOT OTHERWISE CLASSIFIED (HNOC): None as defined under 29 CFR 1910.1200.

#### PHYSICAL / CHEMICAL HAZARDS

No significant hazards.

#### **HEALTH HAZARDS**

High-pressure injection under skin may cause serious damage. Ingestion may cause serious adverse effects and may be fatal. May cause kidney failure and central nervous system effects. Prolonged exposure to elevated concentrations of mist or liquid may cause irritation of the skin, eyes, and respiratory tract.

# **ENVIRONMENTAL HAZARDS**

No significant hazards.

NFPA Hazard ID:	Health:	1	Flammability:	1	Reactivity:	0
HMIS Hazard ID:	Health:	2*	Flammability:	1	Reactivity:	0

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

#### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

This material is defined as a mixture.

# Hazardous Substance(s) or Complex Substance(s) required for disclosure

Name	CAS#		GHS Hazard Codes
		Concentration*	
ETHANOL, 2,2-OXYBIS-	111-46-6	25 - < 50%	H302
MORPHOLINE	110-91-8	0.3 - < 1%	H226, H302, H311, H331, H361(D), H361(F), H314(1B), H402
SODIUM 4 (OR 5) -METHYL-1H-BENZOTRIAZOLE	64665-57-2	0.1 - < 0.2%	H302, H361(D), H314(1B), H401, H411

\* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

As per paragraph (i) of 29 CFR 1910.1200, formulation is considered a trade secret and specific chemical identity and exact percentage (concentration) of composition may have been withheld. Specific chemical identity and exact percentage composition will be provided to health professionals, employees, or designated representatives in accordance with applicable provisions of paragraph (i).

#### **SECTION 4**

FIRST AID MEASURES

INHALATION

Product Name: NYVAC FR 200D Revision Date: 25 Mar 2022 Page 3 of 11



Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device.

# SKIN CONTACT

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

# EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

# INGESTION

Seek immediate medical attention.

# NOTE TO PHYSICIAN

This product contains ethylene glycol and/or diethylene glycol which, if ingested, are metabolized to toxic metabolites by the enzyme alcohol dehydrogenase, for which ethanol and 4-methylpyrazole \{U.S. drug name Fomepizole, trade name Antizol\} are antagonists. Administration of oral or intravenous ethanol or intravenous 4-methylpyrazole may arrest further metabolism of this material and thereby ameliorate the toxicity. Use of ethanol or 4-methylpyrazole does not affect toxic metabolites that are already present and is not a substitute for hemodialysis.

# SECTION 5 FIRE FIGHTING MEASURES

# EXTINGUISHING MEDIA

**Appropriate Extinguishing Media:** Use water fog, alcohol-resistant foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Inappropriate Extinguishing Media: Straight Streams of Water or Regular Foam

#### **FIRE FIGHTING**

**Fire Fighting Instructions:** Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Unusual Fire Hazards:** Pressurized mists may form a flammable mixture. Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

**Hazardous Combustion Products:** Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume

#### **FLAMMABILITY PROPERTIES**

Flash Point [Method]: >100°C (212°F)Flammable Limits (Approximate volume % in air):LEL: N/DUEL: N/DAutoignition Temperature:407°C (765°F)

# **SECTION 6**



Product Name: NYVAC FR 200D Revision Date: 25 Mar 2022 Page 4 of 11

# NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.

#### **PROTECTIVE MEASURES**

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

#### SPILL MANAGEMENT

Land Spill: Stop leak if you can do it without risk. Recover by pumping or with suitable absorbent.

**Water Spill:** Stop leak if you can do it without risk. Seek advice of a specialist This product emulsifies, disperses or is miscible in water.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

# **ENVIRONMENTAL PRECAUTIONS**

Remove debris in path of spill and remove contaminated debris from shoreline and water surface and dispose of according to local regulations. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

#### SECTION 7

#### HANDLING AND STORAGE

#### HANDLING

Avoid all personal contact. Prevent small spills and leakage to avoid slip hazard. Contains amines. Do not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines.

**Static Accumulator:** This material is not a static accumulator.

#### STORAGE

Do not store in open or unlabelled containers.

#### **SECTION 8**

# **EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### **EXPOSURE LIMIT VALUES**

# Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name Form	Limit / Standard	NOTE	Source
---------------------	------------------	------	--------



Product Name: NYVAC FR 200D Revision Date: 25 Mar 2022 Page 5 of 11

ETHANOL, 2,2-OXYBIS-	-	TWA	10 mg/m3			OARS WEEL
MORPHOLINE	-	TWA	70 mg/m3	20 ppm	Skin	OSHA Z1
MORPHOLINE	-	TWA	20 ppm		Skin	ACGIH

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

No biological limits allocated.

# ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Adequate ventilation should be provided so that exposure limits are not exceeded.

# PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No protection is ordinarily required under normal conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include: Chemical/oil resistant clothing is recommended.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.



Product Name: NYVAC FR 200D Revision Date: 25 Mar 2022 Page 6 of 11

# ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

# **SECTION 9**

#### PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

#### **GENERAL INFORMATION**

Physical State:LiquidColor:RedOdor:CharacteristicOdor Threshold:N/D

# IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15 °C): 1.08 [ASTM D1298] Flammability (Solid, Gas): N/A Flash Point [Method]: >100°C (212°F) Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D Autoignition Temperature: 407°C (765°F) **Boiling Point / Range:** 102°C (216°F) Decomposition Temperature: N/D Vapor Density (Air = 1): N/D Vapor Pressure: 1.756 kPa (13.2 mm Hg) at 20 °C Evaporation Rate (n-butyl acetate = 1): N/D pH: 9.5 Log Pow (n-Octanol/Water Partition Coefficient): N/D Solubility in Water: Complete 40 cSt (40 mm2/sec) at 40 °C Viscosity: [ASTM D 445] Oxidizing Properties: See Hazards Identification Section.

#### **OTHER INFORMATION**

Freezing Point:N/DMelting Point:N/DPour Point:-50°C(-58°F)[ASTM D97]

**SECTION 10** 

#### STABILITY AND REACTIVITY

**REACTIVITY:** See sub-sections below.

**STABILITY:** Material is stable under normal conditions.

**CONDITIONS TO AVOID:** Excessive heat. High energy sources of ignition.

MATERIALS TO AVOID: Strong Acids, Strong Bases, Strong oxidizers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.



# **SECTION 11**

# **TOXICOLOGICAL INFORMATION**

# INFORMATION ON TOXICOLOGICAL EFFECTS

Hazard Class	Conclusion / Remarks
Inhalation	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
Ingestion	
Acute Toxicity (Human): LDLo 100 ml	Moderately toxic. Based on assessment of the components.
Skin	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin Corrosion/Irritation: No end point data for material.	Negligible irritation to skin at ambient temperatures. Based on assessment of the components.
Eye	
Serious Eye Damage/Irritation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.
Sensitization	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: No end point data for material.	Not expected to be a skin sensitizer. Based on assessment of the components.
Aspiration: No end point data for material.	Not expected to be an aspiration hazard. Based on physico- chemical properties of the material.
Germ Cell Mutagenicity: No end point data for material.	Not expected to be a germ cell mutagen. Based on assessment of the components.
Carcinogenicity: No end point data for material.	Not expected to cause cancer. Based on assessment of the components.
Reproductive Toxicity: No end point data for material.	Contains a substance that may be a reproductive toxicant. Based on assessment of the components.
Lactation: No end point data for material.	Not expected to cause harm to breast-fed children.
Specific Target Organ Toxicity (STOT)	
Single Exposure: No end point data for material.	Not expected to cause organ damage from a single exposure.
Repeated Exposure: No end point data for material.	Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components.

# TOXICITY FOR SUBSTANCES

NAME	ACUTE TOXICITY
MORPHOLINE	Dermal Lethality: LD50 500 mg/kg (Rabbit); Inhalation Lethality: 4
	hour(s) LC50 8 mg/l (Vapor) (Rat); Oral Lethality: LD50 1900
	mg/kg (Rat)
SODIUM 4 (OR 5) -METHYL-1H-	Oral Lethality: LD50 735 mg/kg (Rat)
BENZOTRIÁZOLÉ	

# **OTHER INFORMATION**

#### Contains:

DIETHYLENE GLYCOL (DEG): Orally, DEG is more toxic to humans than animal test data indicate. Probable lethal



Product Name: NYVAC FR 200D Revision Date: 25 Mar 2022 Page 8 of 11

dose for an adult is about 50 ml (2 oz.), or 2 -3 swallows. Smaller amounts may cause kidney degeneration and failure. Benign urinary bladder tumors were observed in rats, no tumors were observed in mice.

# The following ingredients are cited on the lists below: None.

	REGULATORY LISTS SEA	ARCHED
1 = NTP CARC	3 = IARC 1	5 = IARC 2B
2 = NTP SUS	4 = IARC 2A	6 = OSHA CARC

# SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

#### ECOTOXICITY

Material -- Not expected to be harmful to aquatic organisms.

#### MOBILITY

Material -- Expected to remain in water or migrate through soil.

# PERSISTENCE AND DEGRADABILITY

# **Biodegradation:**

**SECTION 13** 

Material -- Expected to be readily biodegradable.

# Atmospheric Oxidation:

Material -- Expected to degrade rapidly in air

#### **BIOACCUMULATION POTENTIAL**

Material -- Potential to bioaccumulate is low.

#### DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

#### **DISPOSAL RECOMMENDATIONS**

Even though this product is biodegradable, it must not be indiscriminately discarded into the environment. Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

# **REGULATORY DISPOSAL INFORMATION**

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrositivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue



Product Name: NYVAC FR 200D Revision Date: 25 Mar 2022 Page 9 of 11

and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

# SECTION 14 TRANSPORT INFORMATION

- LAND (DOT): Not Regulated for Land Transport
- LAND (TDG): Not Regulated for Land Transport
- **SEA (IMDG):** Not Regulated for Sea Transport according to IMDG-Code

Marine Pollutant: No

**AIR (IATA):** Not Regulated for Air Transport

# **SECTION 15**

# **REGULATORY INFORMATION**

**OSHA HAZARD COMMUNICATION STANDARD:** This material is considered hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200.

**Listed or exempt from listing/notification on the following chemical inventories:** AlIC, DSL, ENCS, IECSC, ISHL, PICCS, TCSI, TSCA

#### Special Cases:

Inventory	Status
KECI	Restrictions Apply

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302

**SARA (311/312) REPORTABLE GHS HAZARD CLASSES:** Acute Toxicity (any route of exposure), Reproductive toxicity

**SARA (313) TOXIC RELEASE INVENTORY:** This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

#### The following ingredients are cited on the lists below:

Chemical Name	CAS Number	List Citations
ETHANOL, 2,2-OXYBIS-	111-46-6	16, 18
MORPHOLINE	110-91-8	1, 4



Product Name: NYVAC FR 200D Revision Date: 25 Mar 2022 Page 10 of 11

# --REGULATORY LISTS SEARCHED--

1 = ACGIH ALL	6 = TSCA 5a2	11 = CA P65 REPRO	16 = MN RTK
2 = ACGIH A1	7 = TSCA 5e	12 = CA RTK	17 = NJ RTK
3 = ACGIH A2	8 = TSCA 6	13 = IL RTK	18 = PA RTK
4 = OSHA Z	9 = TSCA 12b	14 = LA RTK	19 = RI RTK
5 = TSCA 4	10 = CA P65 CARC	15 = MI 293	

Code key: CARC=Carcinogen; REPRO=Reproductive

SECTION 16

. . . . . . . .

#### OTHER INFORMATION

N/D = Not determined, N/A = Not applicable

# **KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):**

H226: Flammable liquid and vapor; Flammable Liquid, Cat 3 H302: Harmful if swallowed; Acute Tox Oral, Cat 4 H311: Toxic in contact with skin; Acute Tox Dermal, Cat 3 H314(1B): Causes severe skin burns and eye damage; Skin Corr/Irritation, Cat 1B H331: Toxic if inhaled; Acute Tox Inh, Cat 3 H361(D): Suspected of damaging the unborn child; Repro Tox, Cat 2 (Develop) H361(F): Suspected of damaging fertility; Repro Tox, Cat 2 (Fertility) H401: Toxic to aquatic life; Acute Env Tox, Cat 2 H402: Harmful to aquatic life; Acute Env Tox, Cat 3 H411: Toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 2

# THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Composition: Component Table information was modified. Section 02: GHS Contains for LABEL\_GHS codes information was modified. Section 11 Substance Toxicology table information was modified. Section 16: HCode Key information was modified.

\_\_\_\_\_

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

-----

Internal Use Only MHC: 2, 0, 0, 0, 0, 0

PPEC: C

DGN: 2007591XDM (1015398)



\_\_\_\_

Product Name: NYVAC FR 200D Revision Date: 25 Mar 2022 Page 11 of 11

Copyright 2002 Exxon Mobil Corporation, All rights reserved