

SAFETY DATA SHEET

SECTION 1	IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING
------------------	---

As of the revision date above, this SDS meets the regulations in the United Kingdom & Ireland.

1.1. PRODUCT IDENTIFIER

Product Name: VISOM 4
Product Description: Severely Treated Base Oils
Product Code: 301010302010, 408118, 710707-60

Registration Name:

Paraffin oils (petroleum), catalytic de-waxed light

Identification Number: (CAS #)64742-71-8

Registration Number:

01-2119485040-48-0004; 01-2119485040-48

1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Intended Use: Base oil

Identified Uses:

Manufacture of substance
Distribution of substance
Use as an intermediate
Formulation and (re)packing of substances and mixtures
Use in Cleaning Agents - Industrial
Lubricants - Industrial
Metal working fluids / rolling oils - Industrial
Lubricants - Professional (Low Release)

See Section 16 for list of REACH Use Descriptors for Identified Uses shown above.

Uses advised against: This product is not recommended for any industrial, professional or consumer use other than the Identified Uses above.

1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Supplier: ExxonMobil Petroleum & Chemical BVBA
POLDERDIJKWEG
B-2030 Antwerpen
Belgium

Product Technical Information:
Supplier General Contact:

(UK) 0800 028 2851 / (IE) 1800 882 024
(UK) 0800 028 2851 / (IE) 1800 882 024

Product Name: VISOM 4
Revision Date: 11 Dec 2019
Page 2 of 40

SDS Internet Address:
E-Mail:
Supplier / Registrant:

www.msds.exxonmobil.com
sds.uk@exxonmobil.com
(BE) +32 3 790 3111

1.4. EMERGENCY TELEPHONE NUMBER

24 Hour Emergency Telephone:
National Poison Control Centre:

(UK) (+44) 870 8200418 / (IE) (+353) 19014670
(UK) 111 / (IE) (+353)1 809 2166

SECTION 2 HAZARDS IDENTIFICATION

2.1. CLASSIFICATION OF SUBSTANCE OR MIXTURE

Classification according to Regulation (EC) No 1272/2008

Aspiration toxicant: Category 1.

H304: May be fatal if swallowed and enters airways.

2.2. LABEL ELEMENTS

Label elements according to Regulation (EC) No 1272/2008

Pictograms:



Signal Word: Danger

Hazard Statements:

H304: May be fatal if swallowed and enters airways.

Precautionary Statements:

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents and container in accordance with local regulations.

Contains: Paraffin oils (petroleum), catalytic de-waxed light

2.3. OTHER HAZARDS

Physical / Chemical Hazards:

No significant hazards.

Product Name: VISOM 4
 Revision Date: 11 Dec 2019
 Page 3 of 40

Health Hazards:

High-pressure injection under skin may cause serious damage. Excessive exposure may result in eye, skin, or respiratory irritation.

Environmental Hazards:

No significant hazards. Material does not meet the criteria for PBT or vPvB in accordance with REACH Annex XIII.

SECTION 3	COMPOSITION / INFORMATION ON INGREDIENTS
------------------	---

3.1. SUBSTANCES

This material is defined as a substance.

Reportable hazardous substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

Name	CAS#	EC#	Registration#	Concentration *	GHS/CLP classification
Paraffin oils (petroleum), catalytic de-waxed light	64742-71-8	265-176-5	01-2119485040-48	100 %	Asp. Tox. 1 H304

Note - any classification in brackets is a GHS building block that was not adopted by the EU in the CLP regulation (No 1272/2008) and therefore is not applicable in the EU or in non-EU countries which have implemented the CLP regulation and is shown for informational purposes only.

Note: See SDS Section 16 for full text of hazard statements.

3.2. MIXTURES Not Applicable. This product is regulated as a substance.

SECTION 4	FIRST AID MEASURES
------------------	---------------------------

4.1. DESCRIPTION OF FIRST AID MEASURES

INHALATION

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

SKIN CONTACT

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

Seek immediate medical attention. Do not induce vomiting.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Local necrosis as evidenced by delayed onset of pain and tissue damage a few hours after injection.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION 5	FIRE FIGHTING MEASURES
------------------	-------------------------------

5.1. EXTINGUISHING MEDIA

Suitable Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Unsuitable Extinguishing Media: Straight streams of water

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Hazardous Combustion Products: Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulphur oxides

5.3. ADVICE FOR FIRE FIGHTERS

Fire Fighting Instructions: Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

FLAMMABILITY PROPERTIES

Flash Point [Method]: >200°C (392°F) [ASTM D-92]

Upper/Lower Flammable Limits (Approximate volume % in air): UEL: 7.0 LEL: 0.9 [Estimated]

Autoignition Temperature: No data available

SECTION 6	ACCIDENTAL RELEASE MEASURES
------------------	------------------------------------

6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 5 of 40

For emergency responders: Respiratory protection: respiratory protection will be necessary only in special cases, e.g., formation of mists. Half-face or full-face respirator with filter(s) for dust/organic vapor or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to hydrocarbons are recommended. Gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

6.2. ENVIRONMENTAL PRECAUTIONS

Large Spills: Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Land Spill: Stop leak if you can do so without risk. Recover by pumping or with suitable absorbent.

Water Spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

6.4. REFERENCES TO OTHER SECTIONS

See Sections 8 and 13.

SECTION 7

HANDLING AND STORAGE

7.1. PRECAUTIONS FOR SAFE HANDLING

Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or earthing procedures. However, bonding and earthing may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

Static Accumulator: This material is a static accumulator.

7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

The type of container used to store the material may affect static accumulation and dissipation. Do not store in open or unlabelled containers.

7.3. SPECIFIC END USES

Section 1 informs about identified end-uses. No industrial or sector specific guidance available.

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 7 of 40

Paraffin oils (petroleum), catalytic de-waxed light	NA	NA	NA	NA	NA	NA	9.33 mg / kg (food)
---	----	----	----	----	----	----	---------------------

8.2. EXPOSURE CONTROLS

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions.

Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No special requirements under ordinary conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

No protection is ordinarily required under normal conditions of use.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Product Name: VISOM 4
Revision Date: 11 Dec 2019
Page 8 of 40

For Summary of Risk Management Measures across all identified uses, see Annex.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid
Colour: Colourless
Odour: Characteristic
Odour Threshold: No data available
pH: Not technically feasible
Melting Point: Not technically feasible
Freezing Point: No data available
Initial Boiling Point / and Boiling Range: No data available
Flash Point [Method]: >200°C (392°F) [ASTM D-92]
Evaporation Rate (n-butyl acetate = 1): No data available
Flammability (Solid, Gas): Not technically feasible
Upper/Lower Flammable Limits (Approximate volume % in air): UEL: 7.0 LEL: 0.9 [Estimated]
Vapour Pressure: < 0.013 kPa (0.1 mm Hg) at 20 °C [Estimated]
Vapour Density (Air = 1): > 2 at 101 kPa [Estimated]
Relative Density (at 15 °C): 0.82 [ASTM D4052]
Solubility(ies): water Negligible
Partition coefficient (n-Octanol/Water Partition Coefficient): > 3.5 [Estimated]
Autoignition Temperature: No data available
Decomposition Temperature: No data available
Viscosity: 16.8 cSt (16.8 mm²/sec) at 40°C | 4 cSt (4 mm²/sec) at 100°C [ASTM D 445]
Explosive Properties: None
Oxidizing Properties: None

9.2. OTHER INFORMATION

Pour Point: -18°C (0°F) [ASTM D97]
DMSO Extract (mineral oil only), IP-346: < 3 %wt

SECTION 10 STABILITY AND REACTIVITY

10.1. REACTIVITY: See sub-sections below.

Product Name: VISOM 4
 Revision Date: 11 Dec 2019
 Page 9 of 40

10.2. CHEMICAL STABILITY: Material is stable under normal conditions.

10.3. POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization will not occur.

10.4. CONDITIONS TO AVOID: Excessive heat. High energy sources of ignition.

10.5. INCOMPATIBLE MATERIALS: Strong oxidisers

10.6. HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

SECTION 11	TOXICOLOGICAL INFORMATION
-------------------	----------------------------------

11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

Hazard Class	Conclusion / Remarks
Inhalation	
Acute Toxicity: (Rat) LC50 > 5000 mg/m ³ Test scores or other study results do not meet criteria for classification.	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 403
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures. Based on assessment of the components.
Ingestion	
Acute Toxicity (Rat): LD50 > 5000 mg/kg Test scores or other study results do not meet criteria for classification.	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 401
Skin	
Acute Toxicity (Rabbit): LD50 > 5000 mg/kg Test scores or other study results do not meet criteria for classification.	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 402
Skin Corrosion/Irritation (Rabbit): Data available. Test scores or other study results do not meet criteria for classification.	Negligible irritation to skin at ambient temperatures. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 404
Eye	
Serious Eye Damage/Irritation (Rabbit): Data available. Test scores or other study results do not meet criteria for classification.	May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 405
Sensitisation	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: Data available. Test scores or other study results do not meet criteria for classification.	Not expected to be a skin sensitizer. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 406
Aspiration: Data available.	May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material.
Germ Cell Mutagenicity: Data available. Test scores or other study results do not meet criteria for classification.	Not expected to be a germ cell mutagen. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 471 473 474 476
Carcinogenicity: Data available. Test scores or other study results do not meet criteria for classification.	Not expected to cause cancer. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 451 453
Reproductive Toxicity: Data available. Test scores or other study results do not meet criteria for classification.	Not expected to be a reproductive toxicant. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 414 421

Product Name: VISOM 4
 Revision Date: 11 Dec 2019
 Page 10 of 40

Lactation: No end point data for material.	Not expected to cause harm to breast-fed children.
Specific Target Organ Toxicity (STOT)	
Single Exposure: Data available. Test scores or other study results do not meet criteria for classification.	Not expected to cause organ damage from a single exposure. Based on test data for structurally similar materials.
Repeated Exposure: Data available. Test scores or other study results do not meet criteria for classification.	Not expected to cause organ damage from prolonged or repeated exposure. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 408 410 411 412 453

OTHER INFORMATION

For the product itself:

Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitising in test animals.

SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

12.1. TOXICITY

Material -- Not expected to be harmful to aquatic organisms.

12.2. PERSISTENCE AND DEGRADABILITY

Biodegradation:

Material -- Expected to be inherently biodegradable

12.3. BIOACCUMULATIVE POTENTIAL

Material -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

12.4. MOBILITY IN SOIL

Material -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

Material -- Low potential to migrate through soil.

12.5. PERSISTENCE, BIOACCUMULATION AND TOXICITY FOR SUBSTANCE(S)

Material does not meet the Reach Annex XIII criteria for PBT or vPvB.

12.6. OTHER ADVERSE EFFECTS

No adverse effects are expected.

ECOLOGICAL DATA

Ecotoxicity

Test	Duration	Organism Type	Test Results
Aquatic - Acute Toxicity	48 hour(s)	Daphnia magna	EL0 1000 - 10000 mg/l: data for similar materials
Aquatic - Acute Toxicity	96 hour(s)	Pimephales promelas	LL0 100 mg/l: data for similar materials
Aquatic - Acute Toxicity	72 hour(s)	Pseudokirchneriella subcapitata	EL0 100 mg/l: data for similar materials
Aquatic - Chronic Toxicity	21 day(s)	Daphnia magna	NOELR 10 - 1000 mg/l: data for similar materials
Aquatic - Chronic Toxicity	72 hour(s)	Pseudokirchneriella subcapitata	NOELR 100 mg/l: data for similar materials

Persistence, Degradability and Bioaccumulation Potential

Media	Test Type	Duration	Test Results: Basis
Water	Ready Biodegradability	28 day(s)	Percent Degraded < 60 : similar material

SECTION 13

DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

13.1. WASTE TREATMENT METHODS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Protect the environment. Dispose of used oil at designated sites. Minimize skin contact. Do not mix used oils with solvents, brake fluids or coolants.

European Waste Code: 13 02 05*

NOTE: These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste disposal code(s).

This material is considered as hazardous waste pursuant to Directive 91/689/EEC on hazardous waste, and subject to the provisions of that Directive unless Article 1(5) of that Directive applies.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with

Product Name: VISOM 4
Revision Date: 11 Dec 2019
Page 12 of 40

governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14 TRANSPORT INFORMATION

LAND (ADR/RID): 14.1-14.6 Not Regulated for Land Transport

INLAND WATERWAYS (ADN): 14.1-14.6 Not Regulated for Inland Waterways Transport

SEA (IMDG): 14.1-14.6 Not Regulated for Sea Transport according to IMDG-Code

SEA (MARPOL 73/78 Convention - Annex II):

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not classified according to Annex II

AIR (IATA): 14.1-14.6 Not Regulated for Air Transport

SECTION 15 REGULATORY INFORMATION

REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS

Listed or exempt from listing/notification on the following chemical inventories (May contain substance(s) subject to notification to the EPA Active TSCA inventory prior to import to USA): AICS, DSL, ENCS, IECSC, ISHL, KECI, PICCS, TCSI, TSCA

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

Applicable EU Directives and Regulations:

1907/2006 [... on the Registration, Evaluation, Authorisation and Restriction of Chemicals ... and amendments thereto]
1272/2008 [on classification, labelling and packaging of substances and mixtures.. and amendments thereto]

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 13 of 40

15.2. CHEMICAL SAFETY ASSESSMENT

REACH Information: A Chemical Safety Assessment has been carried out for one or more substances present in the material.

SECTION 16	OTHER INFORMATION
-------------------	--------------------------

IDENTIFIED USES:

Manufacture of substance (PROC1, PROC15, PROC2, PROC3, PROC4, PROC8a, PROC8b, SU10, SU3, SU8, SU9)

Distribution of substance (PROC1, PROC15, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, SU3, SU8, SU9)

Use as an intermediate (PROC1, PROC15, PROC2, PROC3, PROC4, PROC8a, PROC8b, SU3, SU8, SU9)

Formulation and (re)packing of substances and mixtures (PROC1, PROC14, PROC15, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, SU10, SU3)

Use in Cleaning Agents - Industrial (PROC1, PROC10, PROC13, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, SU3,)

Lubricants - Industrial (PROC1, PROC10, PROC13, PROC17, PROC18, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, SU3)

Metal working fluids / rolling oils - Industrial (PROC1, PROC10, PROC13, PROC17, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, SU3)

Lubricants - Professional (Low Release) (PROC1, PROC10, PROC11, PROC13, PROC17, PROC18, PROC2, PROC20, PROC3, PROC4, PROC8a, PROC8b, PROC9, SU22)

REFERENCES: Sources of information used in preparing this SDS included one or more of the following: results from in house or supplier toxicology studies, CONCAWE Product Dossiers, publications from other trade associations, such as the EU Hydrocarbon Solvents REACH Consortium, U.S. HPV Program Robust Summaries, the EU IUCLID Data Base, U.S. NTP publications, and other sources, as appropriate.

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

Acronym	Full text
N/A	Not applicable
N/D	Not determined
NE	Not established
VOC	Volatile Organic Compound
AICS	Australian Inventory of Chemical Substances
AIHA WEEL	American Industrial Hygiene Association Workplace Environmental Exposure Limits
ASTM	ASTM International, originally known as the American Society for Testing and Materials (ASTM)
DSL	Domestic Substance List (Canada)
EINECS	European Inventory of Existing Commercial Substances
ELINCS	European List of Notified Chemical Substances
ENCS	Existing and new Chemical Substances (Japanese inventory)
IECSC	Inventory of Existing Chemical Substances in China
KECI	Korean Existing Chemicals Inventory
NDSL	Non-Domestic Substances List (Canada)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances
TLV	Threshold Limit Value (American Conference of Governmental Industrial Hygienists)
TSCA	Toxic Substances Control Act (U.S. inventory)
UVCB	Substances of Unknown or Variable composition, Complex reaction products or Biological materials
LC	Lethal Concentration
LD	Lethal Dose
LL	Lethal Loading
EC	Effective Concentration

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 14 of 40

EL	Effective Loading
NOEC	No Observable Effect Concentration
NOELR	No Observable Effect Loading Rate

KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

Asp. Tox. 1 H304: May be fatal if swallowed and enters airways; Aspiration, Cat 1

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Agrochemical uses - Consumer: Annex Information information was deleted.
Agrochemical uses - Consumer: Section 1: Use Table information was deleted.
Agrochemical uses - Professional: Annex Information information was deleted.
Agrochemical uses - Professional: Section 1: Use Table information was deleted.
Distribution of substance: Annex Information information was modified.
Explosives manufacture & use: Annex Information information was deleted.
Explosives manufacture & use: Section 1: Use Table information was deleted.
Formulation and (re)packing of substances and mixtures: Annex Information information was modified.
Functional Fluids - Consumer: Annex Information information was deleted.
Functional Fluids - Consumer: Section 1: Use Table information was deleted.
Functional Fluids - Industrial: Annex Information information was deleted.
Functional Fluids - Industrial: Section 1: Use Table information was deleted.
Functional Fluids - Professional: Annex Information information was deleted.
Functional Fluids - Professional: Section 1: Use Table information was deleted.
Lubricants - Consumer (High Release): Annex Information information was deleted.
Lubricants - Consumer (High Release): Section 1: Use Table information was deleted.
Lubricants - Consumer (Low Release): Annex Information information was deleted.
Lubricants - Consumer (Low Release): Section 1: Use Table information was deleted.
Lubricants - Industrial: Annex Information information was modified.
Lubricants - Professional (High Release): Annex Information information was deleted.
Lubricants - Professional (High Release): Section 1: Use Table information was deleted.
Lubricants - Professional (Low Release): Annex Information information was modified.
Metal working fluids / rolling oils - Industrial: Annex Information information was modified.
Metal working fluids / rolling oils - Professional: Annex Information information was deleted.
Metal working fluids / rolling oils - Professional: Section 1: Use Table information was deleted.
Mining chemicals: Annex Information information was deleted.
Mining chemicals: Section 1: Use Table information was deleted.
Polymer processing - Industrial: Annex Information information was deleted.
Polymer processing - Industrial: Section 1: Use Table information was deleted.
Polymer processing - Professional: Annex Information information was deleted.
Polymer processing - Professional: Section 1: Use Table information was deleted.
Road and construction applications: Annex Information information was deleted.
Road and construction applications: Section 1: Use Table information was deleted.
Rubber production and processing: Annex Information information was deleted.
Rubber production and processing: Section 1: Use Table information was deleted.
Section 01: Company Contact Methods information was modified.
Section 01: Company Emergency Contact information was modified.
Section 08: Exposure Limits Table information was modified.
Section 12: PBT/vPvB information was modified.
Section 12: information was modified.
Use as a fuel - Consumer: Annex Information information was deleted.
Use as a fuel - Consumer: Section 1: Use Table information was deleted.

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 15 of 40

Use as a fuel - Industrial: Annex Information information was deleted.
Use as a fuel - Industrial: Section 1: Use Table information was deleted.
Use as a fuel - Professional: Annex Information information was deleted.
Use as a fuel - Professional: Section 1: Use Table information was deleted.
Use as binders and release agents - Industrial: Annex Information information was deleted.
Use as binders and release agents - Industrial: Section 1: Use Table information was deleted.
Use as binders and release agents - Professional: Annex Information information was deleted.
Use as binders and release agents - Professional: Section 1: Use Table information was deleted.
Use in Cleaning Agents - Consumer: Annex Information information was deleted.
Use in Cleaning Agents - Consumer: Section 1: Use Table information was deleted.
Use in Cleaning Agents - Industrial: Annex Information information was modified.
Use in Cleaning Agents - Professional: Annex Information information was deleted.
Use in Cleaning Agents - Professional: Section 1: Use Table information was deleted.
Use in Coatings - Consumer: Annex Information information was deleted.
Use in Coatings - Consumer: Section 1: Use Table information was deleted.
Use in Coatings - Industrial: Annex Information information was deleted.
Use in Coatings - Industrial: Section 1: Use Table information was deleted.
Use in Coatings - Professional: Annex Information information was deleted.
Use in Coatings - Professional: Section 1: Use Table information was deleted.
Use in laboratories - Industrial: Annex Information information was deleted.
Use in laboratories - Industrial: Section 1: Use Table information was deleted.
Use in laboratories - Professional: Annex Information information was deleted.
Use in laboratories - Professional: Section 1: Use Table information was deleted.
Use in oil field drilling and production operations - Industrial: Annex Information information was deleted.
Use in oil field drilling and production operations - Industrial: Section 1: Use Table information was deleted.
Use in oil field drilling and production operations - Professional: Annex Information information was deleted.
Use in oil field drilling and production operations - Professional: Section 1: Use Table information was deleted.
Water treatment chemicals - Industrial: Annex Information information was deleted.
Water treatment chemicals - Industrial: Section 1: Use Table information was deleted.
Water treatment chemicals - Professional: Annex Information information was deleted.
Water treatment chemicals - Professional: Section 1: Use Table information was deleted.

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

Internal Use Only

MHC: 2A, 0B, 0, 0, 0, 0

PPEC: A

DGN: 2027265XGB (1018781)

ANNEX

Section 1 Exposure Scenario Title	
Title:	
Manufacture of substance	
Use Descriptor	
Sector(s) of Use	SU10, SU3, SU8, SU9
Process Categories	PROC1, PROC15, PROC2, PROC3, PROC4, PROC8a, PROC8b
Environmental Release Categories	ERC1, ERC4
Specific Environmental Release Category	ESVOC 1.1.v1
Processes, tasks, activities covered	
Manufacture of the substance or use as an intermediate, process chemical or extracting agent. Includes recycling/recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).	
Section 2 Operational conditions and risk management measures	
Section 2.1 Control of worker exposure	
Product Characteristic	
Liquid	
Duration, frequency and amount	
Covers daily exposures up to 8 hours (unless stated differently)[G2] Covers percentage substance in the product up to 100 %[G13]	
Other given operational conditions affecting workers exposure	
Assumes a good basic standard of occupational hygiene is implemented [G1] Operation is carried out at elevated temperature (>20 C above ambient temperature)[OC7]	
Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions	
(only required controls to demonstrate safe use listed)	
General measures (Aspiration Hazard)	
The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting.	
General exposures (closed systems) PROC1	
No other specific measures identified.	
General exposures (closed systems) PROC2	
No other specific measures identified.	
General exposures (closed systems) PROC3	
No other specific measures identified.	
General exposures (open systems) PROC4	
No other specific measures identified.	
Process sampling PROC3	
No other specific measures identified.	
Laboratory activities PROC15	

Product Name: VISOM 4
 Revision Date: 11 Dec 2019
 Page 17 of 40

<p>No other specific measures identified.</p> <p>Bulk transfers (closed systems) PROC8b No other specific measures identified.</p> <p>Bulk transfers (open systems) PROC8b No other specific measures identified.</p> <p>Equipment cleaning and maintenance PROC8a Drain down system prior to equipment break-in or maintenance.</p> <p>Bulk product storage PROC1 Store substance within a closed system.</p> <p>Bulk product storage PROC2 Store substance within a closed system.</p>
<p>Section 2.2 Control of environmental exposure</p>
<p>Product characteristics</p> <p>Predominantly hydrophobic. Substance is complex UVCB.</p>
<p>Duration, frequency and amount</p> <p>Annual site tonnage (tonnes/year): 600000 tons/yr Continuous release. Emission Days (days/year): 300 days/yr Fraction of EU tonnage used in region: 0.1 Fraction of Regional tonnage used Locally: 1 Maximum daily site tonnage (kg/d): 2000000 kg / day Regional use tonnage (tonnes/year): 850000 tons/yr</p>
<p>Environmental factors not influenced by risk management</p> <p>Local freshwater dilution factor [EF1] 10 Local marine water dilution factor: [EF2] 100</p>
<p>Other given operational conditions affecting environmental exposure</p> <p>Release fraction to air from process (initial release prior to RMM): 0.0001 Release fraction to soil from process (initial release prior to RMM): 0.0001 Release fraction to wastewater from process (initial release prior to RMM): 0.00001</p>
<p>Technical conditions and measures at process level (source) to prevent release</p> <p>Common practices vary across sites thus conservative process release estimates used.</p>
<p>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</p> <p>If discharging to domestic sewage treatment plant, no onsite wastewater treatment required. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of =: >= 0 % Risk from environmental exposure is driven by Treat air emissions to provide a typical removal (or abatement?) efficiency of: 90 % Treat onsite wastewater (prior to receiving water discharge) to provide the required removal (or abatement) efficiency of =: >= 84.8 %</p>
<p>Organisation measures to prevent/limit release from site</p> <p>Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from wastewater. Sludge should be incinerated, contained or reclaimed.</p>
<p>Conditions and measures related to municipal sewage treatment plant</p> <p>Assumed domestic sewage treatment plant effluent flow is:[STP5] 10000 m3/day Estimated substance removal from wastewater via domestic sewage treatment is: 94.7 % Not applicable as there is no release to wastewater. The maximum allowable site tonnage (MSafe) based on domestic sewage plant effluent release is: 5700000 kg / day Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs is: 94.7 %</p>
<p>Conditions and measures related to external treatment of waste for disposal</p>

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 18 of 40

During manufacturing no waste of the substance is generated [ETW4]
Conditions and measures related to external recovery of waste
During manufacturing no waste of the substance is generated [ERW2]
Section 3 Exposure Estimation
3.1. Health
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21]
3.2. Environment
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.[EE2]
Section 4 Guidance to check compliance with the Exposure Scenario
4.1. Health
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. [G32]
Available hazard data do not support the need for a DNEL to be established for other health effects.[G36]
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. [G22]
Risk Management Measures are based on qualitative risk characterisation. [G37]
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.[G23]
4.2. Environment
Further details on scaling and control technologies are provided in factsheet
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
Scaled local assessments for EU refineries have been performed using site-specific data and are attached in PETRORISK file - 'Site-Specific Production' worksheet. [DSU6]

Product Name: VISOM 4
 Revision Date: 11 Dec 2019
 Page 19 of 40

Section 1 Exposure Scenario Title	
Title:	
Distribution of substance	
Use Descriptor	
Sector(s) of Use	SU3, SU8, SU9
Process Categories	PROC1, PROC15, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9
Environmental Release Categories	ERC1, ERC2, ERC3, ERC4, ERC5, ERC6A, ERC6B, ERC6C, ERC6D, ERC7
Specific Environmental Release Category	ESVOC 1.1.v1
Processes, tasks, activities covered	
Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading, distribution and associated laboratory activities.	
Section 2 Operational conditions and risk management measures	
Section 2.1 Control of worker exposure	
Product Characteristic	
Liquid	
Duration, frequency and amount	
Covers daily exposures up to 8 hours (unless stated differently)[G2] Covers percentage substance in the product up to 100 %[G13]	
Other given operational conditions affecting workers exposure	
Assumes a good basic standard of occupational hygiene is implemented [G1] Operation is carried out at elevated temperature (>20 C above ambient temperature)[OC7]	
Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions (only required controls to demonstrate safe use listed)	
<p>General measures (Aspiration Hazard) The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting.</p> <p>General exposures (closed systems) PROC1 No other specific measures identified.</p> <p>General exposures (closed systems) PROC2 No other specific measures identified.</p> <p>General exposures (closed systems) PROC3 No other specific measures identified.</p> <p>General exposures (open systems) PROC4 No other specific measures identified.</p> <p>Process sampling PROC3 No other specific measures identified.</p> <p>Laboratory activities PROC15 No other specific measures identified.</p> <p>Bulk transfers (closed systems) PROC8b No other specific measures identified.</p> <p>Bulk transfers (open systems) PROC8b No other specific measures identified.</p> <p>Drum and small package filling PROC9</p>	

Product Name: VISOM 4
 Revision Date: 11 Dec 2019
 Page 20 of 40

No other specific measures identified.
Equipment cleaning and maintenance PROC8a Drain down system prior to equipment break-in or maintenance.
Storage PROC1 Store substance within a closed system.
Storage PROC2 Store substance within a closed system.
Section 2.2 Control of environmental exposure
Product characteristics Predominantly hydrophobic. Substance is complex UVCB.
Duration, frequency and amount Annual site tonnage (tonnes/year): 1700 tons/yr Continuous release. Emission Days (days/year): 100 days/yr Fraction of EU tonnage used in region: 0.1 Fraction of Regional tonnage used Locally: 0.002 Maximum daily site tonnage (kg/d): 17000 kg / day Regional use tonnage (tonnes/year): 850000 tons/yr
Environmental factors not influenced by risk management Local freshwater dilution factor [EF1] 10 Local marine water dilution factor: [EF2] 100
Other given operational conditions affecting environmental exposure Release fraction to air from process (initial release prior to RMM): 0.0001 Release fraction to soil from process (initial release prior to RMM): 0.00001 Release fraction to wastewater from process (initial release prior to RMM): 0.0000001
Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil If discharging to domestic sewage treatment plant, no onsite wastewater treatment required. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of =: >= 0 % Risk from environmental exposure is driven by Treat air emissions to provide a typical removal (or abatement?) efficiency of: 90 % Treat onsite wastewater (prior to receiving water discharge) to provide the required removal (or abatement) efficiency of =: >= 64.4 %
Organisation measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Conditions and measures related to municipal sewage treatment plant Assumed domestic sewage treatment plant effluent flow is:[STP5] 2000 m3/day Estimated substance removal from wastewater via domestic sewage treatment is: 94.7 % Not applicable as there is no release to wastewater. The maximum allowable site tonnage (MSafe) based on domestic sewage plant effluent release is: 110000 kg / day Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs is: 94.7 %
Conditions and measures related to external treatment of waste for disposal External treatment and disposal of waste should comply with applicable local and/or national regulations [ETW3]
Conditions and measures related to external recovery of waste External recovery and recycling of waste should comply with applicable local and/or national regulations [ERW1]
Section 3 Exposure Estimation
3.1. Health

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 21 of 40

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21]
3.2. Environment
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.[EE2]
Section 4 Guidance to check compliance with the Exposure Scenario
4.1. Health
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. [G32] Available hazard data do not support the need for a DNEL to be established for other health effects.[G36] Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. [G22] Risk Management Measures are based on qualitative risk characterisation. [G37] Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.[G23]
4.2. Environment
Further details on scaling and control technologies are provided in factsheet Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 22 of 40

Section 1 Exposure Scenario Title	
Title:	
Use as an intermediate	
Use Descriptor	
Sector(s) of Use	SU3, SU8, SU9
Process Categories	PROC1, PROC15, PROC2, PROC3, PROC4, PROC8a, PROC8b
Environmental Release Categories	ERC6A
Specific Environmental Release Category	ESVOC 1.1.v1
Processes, tasks, activities covered	
Use as an intermediate (not related to Strictly Controlled Conditions). Includes incidental exposures during recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).	
Section 2 Operational conditions and risk management measures	
Section 2.1 Control of worker exposure	
Product Characteristic	
Liquid	
Duration, frequency and amount	
Covers daily exposures up to 8 hours (unless stated differently)[G2]	
Covers percentage substance in the product up to 100 %[G13]	
Other given operational conditions affecting workers exposure	
Assumes a good basic standard of occupational hygiene is implemented [G1]	
Operation is carried out at elevated temperature (>20 C above ambient temperature)[OC7]	
Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions (only required controls to demonstrate safe use listed)	
General measures (Aspiration Hazard)	
The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting.	
General exposures (closed systems) PROC1	
No other specific measures identified.	
General exposures (closed systems) PROC2	
No other specific measures identified.	
General exposures (closed systems) PROC3	
No other specific measures identified.	
General exposures (open systems) PROC4	
No other specific measures identified.	
Process sampling PROC3	
No other specific measures identified.	
Laboratory activities PROC15	
No other specific measures identified.	
Bulk transfers (closed systems) PROC8b	
No other specific measures identified.	
Bulk transfers (open systems) PROC8b	
No other specific measures identified.	
Equipment cleaning and maintenance PROC8a	

Product Name: VISOM 4
 Revision Date: 11 Dec 2019
 Page 23 of 40

<p>Drain down system prior to equipment break-in or maintenance.</p> <p>Bulk product storage PROC1 Store substance within a closed system.</p> <p>Bulk product storage PROC2 Store substance within a closed system.</p>
<p>Section 2.2 Control of environmental exposure</p>
<p>Product characteristics</p> <p>Predominantly hydrophobic. Substance is complex UVCB.</p>
<p>Duration, frequency and amount</p> <p>Annual site tonnage (tonnes/year): 1500 tons/yr Continuous release. Emission Days (days/year): 100 days/yr Fraction of EU tonnage used in region: 0.1 Fraction of Regional tonnage used Locally: 1 Maximum daily site tonnage (kg/d): 15000 kg / day Regional use tonnage (tonnes/year): 1500 tons/yr</p>
<p>Environmental factors not influenced by risk management</p> <p>Local freshwater dilution factor [EF1] 10 Local marine water dilution factor: [EF2] 100</p>
<p>Other given operational conditions affecting environmental exposure</p> <p>Release fraction to air from process (initial release prior to RMM): 0.00001 Release fraction to soil from process (initial release prior to RMM): 0.001 Release fraction to wastewater from process (initial release prior to RMM): 0.00001</p>
<p>Technical conditions and measures at process level (source) to prevent release</p> <p>Common practices vary across sites thus conservative process release estimates used.</p>
<p>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</p> <p>If discharging to domestic sewage treatment plant, no onsite wastewater treatment required. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of =: >= 0 % Risk from environmental exposure is driven by Treat air emissions to provide a typical removal (or abatement?) efficiency of: 80 % Treat onsite wastewater (prior to receiving water discharge) to provide the required removal (or abatement) efficiency of =: >= 66.2 %</p>
<p>Organisation measures to prevent/limit release from site</p> <p>Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from wastewater. Sludge should be incinerated, contained or reclaimed.</p>
<p>Conditions and measures related to municipal sewage treatment plant</p> <p>Assumed domestic sewage treatment plant effluent flow is:[STP5] 2000 m3/day Estimated substance removal from wastewater via domestic sewage treatment is: 94.7 % Not applicable as there is no release to wastewater. The maximum allowable site tonnage (MSafe) based on domestic sewage plant effluent release is: 98000 kg / day Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs is: 94.7 %</p>
<p>Conditions and measures related to external treatment of waste for disposal</p> <p>This substance is consumed during use and no waste of the substance is generated [ETW5]</p>
<p>Conditions and measures related to external recovery of waste</p> <p>This substance is consumed during use and no waste of the substance is generated [ERW3]</p>
<p>Section 3 Exposure Estimation</p>
<p>3.1. Health</p> <p>The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21]</p>

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 24 of 40

3.2. Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.[EE2]

Section 4 Guidance to check compliance with the Exposure Scenario

4.1. Health

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. [G32]

Available hazard data do not support the need for a DNEL to be established for other health effects.[G36]

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. [G22]

Risk Management Measures are based on qualitative risk characterisation. [G37]

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.[G23]

4.2. Environment

Further details on scaling and control technologies are provided in factsheet

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Section 1 Exposure Scenario Title	
Title:	
Formulation and (re)packing of substances and mixtures	
Use Descriptor	
Sector(s) of Use	SU10, SU3
Process Categories	PROC1, PROC14, PROC15, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9
Environmental Release Categories	ERC2
Specific Environmental Release Category	ESVOC 1.1.v1
Processes, tasks, activities covered	
Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.	
Section 2 Operational conditions and risk management measures	
Section 2.1 Control of worker exposure	
Product Characteristic	
Liquid	
Duration, frequency and amount	
Covers daily exposures up to 8 hours (unless stated differently)[G2] Covers percentage substance in the product up to 100 %[G13]	
Other given operational conditions affecting workers exposure	
Assumes a good basic standard of occupational hygiene is implemented [G1] Operation is carried out at elevated temperature (>20 C above ambient temperature)[OC7]	
Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions (only required controls to demonstrate safe use listed)	
<p>General measures (Aspiration Hazard) The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting.</p> <p>General exposures (closed systems) PROC1 No other specific measures identified.</p> <p>General exposures (closed systems) PROC2 No other specific measures identified.</p> <p>General exposures (closed systems) PROC3 No other specific measures identified.</p> <p>General exposures (open systems) PROC4 No other specific measures identified.</p> <p>Batch processes at elevated temperatures Use in contained batch processes PROC3 No other specific measures identified.</p> <p>Process sampling PROC3 No other specific measures identified.</p> <p>Laboratory activities PROC15 No other specific measures identified.</p> <p>Bulk transfers Dedicated facility PROC8b No other specific measures identified.</p> <p>Mixing operations (open systems) PROC5</p>	

Product Name: VISOM 4
 Revision Date: 11 Dec 2019
 Page 26 of 40

<p>No other specific measures identified.</p> <p>Manual Transfer from/pouring from containers Non-dedicated facility PROC8a</p> <p>No other specific measures identified.</p> <p>Drum/batch transfers Dedicated facility PROC8b</p> <p>No other specific measures identified.</p> <p>Production of preparations or articles by tableting, compression, extrusion, pelettisation PROC14</p> <p>No other specific measures identified.</p> <p>Drum and small package filling PROC9</p> <p>No other specific measures identified.</p> <p>Equipment cleaning and maintenance PROC8a</p> <p>Drain down system prior to equipment break-in or maintenance.</p> <p>Storage PROC1</p> <p>Store substance within a closed system.</p> <p>Storage PROC2</p> <p>Store substance within a closed system.</p>
<p>Section 2.2 Control of environmental exposure</p>
<p>Product characteristics</p> <p>Predominantly hydrophobic. Substance is complex UVCB.</p>
<p>Duration, frequency and amount</p> <p>Annual site tonnage (tonnes/year): 30000 tons/yr Continuous release. Emission Days (days/year): 300 days/yr Fraction of EU tonnage used in region: 0.1 Fraction of Regional tonnage used Locally: 1 Maximum daily site tonnage (kg/d): 100000 kg / day Regional use tonnage (tonnes/year): 850000 tons/yr</p>
<p>Environmental factors not influenced by risk management</p> <p>Local freshwater dilution factor [EF1] 10 Local marine water dilution factor: [EF2] 100</p>
<p>Other given operational conditions affecting environmental exposure</p> <p>Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements): [OOC11] 0.0025 Release fraction to soil from process (initial release prior to RMM): 0.0001 Release fraction to wastewater from process (initial release prior to RMM): 0.000005</p>
<p>Technical conditions and measures at process level (source) to prevent release</p> <p>Common practices vary across sites thus conservative process release estimates used.</p>
<p>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</p> <p>If discharging to domestic sewage treatment plant, no onsite wastewater treatment required. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of =: >= 0 % Risk from environmental exposure is driven by Treat air emissions to provide a typical removal (or abatement?) efficiency of: 0 % Treat onsite wastewater (prior to receiving water discharge) to provide the required removal (or abatement) efficiency of =: >= 69.5 %</p>
<p>Organisation measures to prevent/limit release from site</p> <p>Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from wastewater. Sludge should be incinerated, contained or reclaimed.</p>
<p>Conditions and measures related to municipal sewage treatment plant</p> <p>Assumed domestic sewage treatment plant effluent flow is:[STP5] 2000 m3/day</p>

Product Name: VISOM 4
 Revision Date: 11 Dec 2019
 Page 27 of 40

Estimated substance removal from wastewater via domestic sewage treatment is: 94.7 % Not applicable as there is no release to wastewater. The maximum allowable site tonnage (MSafe) based on domestic sewage plant effluent release is: 570000 kg / day Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs is: 94.7 %
Conditions and measures related to external treatment of waste for disposal
External treatment and disposal of waste should comply with applicable local and/or national regulations [ETW3]
Conditions and measures related to external recovery of waste
External recovery and recycling of waste should comply with applicable local and/or national regulations [ERW1]
Section 3 Exposure Estimation
3.1. Health
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21]
3.2. Environment
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.[EE2]
Section 4 Guidance to check compliance with the Exposure Scenario
4.1. Health
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. [G32] Available hazard data do not support the need for a DNEL to be established for other health effects.[G36] Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. [G22] Risk Management Measures are based on qualitative risk characterisation. [G37] Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.[G23]
4.2. Environment
Further details on scaling and control technologies are provided in factsheet Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 28 of 40

Section 1 Exposure Scenario Title	
Title:	
Use in Cleaning Agents - Industrial	
Use Descriptor	
Sector(s) of Use	SU3
Process Categories	PROC1, PROC10, PROC13, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b
Environmental Release Categories	ERC4
Specific Environmental Release Category	ESVOC 1.1.v1 ,ESVOC 4.4a.v1
Processes, tasks, activities covered	
Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.	
Section 2 Operational conditions and risk management measures	
Section 2.1 Control of worker exposure	
Product Characteristic	
Liquid	
Duration, frequency and amount	
Covers daily exposures up to 8 hours (unless stated differently)[G2] Covers percentage substance in the product up to 100 %[G13]	
Other given operational conditions affecting workers exposure	
Assumes a good basic standard of occupational hygiene is implemented [G1] Operation is carried out at elevated temperature (>20 C above ambient temperature)[OC7]	
Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions (only required controls to demonstrate safe use listed)	
General measures (Aspiration Hazard)	
The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting.	
Bulk transfers Dedicated facility PROC8b	
No other specific measures identified.	
Automated process with (semi) closed systems Use in contained systems PROC2	
No other specific measures identified.	
Filling / preparation of equipment from drums or containers Dedicated facility PROC8b	
No other specific measures identified.	
Use in contained batch processes Automated process with (semi) closed systems Elevated temperature PROC3	
No other specific measures identified.	
Dipping, immersion and pouring PROC13	
No other specific measures identified.	
Cleaning with low-pressure washers PROC10	
No other specific measures identified.	
Cleaning with high pressure washers PROC7	
Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.	
Manual Surfaces Cleaning No spraying PROC10	
No other specific measures identified.	

<p>Equipment cleaning and maintenance PROC8a Drain down system prior to equipment break-in or maintenance.</p> <p>Storage PROC1 Store substance within a closed system.</p> <p>Storage PROC2 Store substance within a closed system.</p>
<p>Section 2.2 Control of environmental exposure</p>
<p>Product characteristics Predominantly hydrophobic. Substance is complex UVCB.</p>
<p>Duration, frequency and amount Annual site tonnage (tonnes/year): 100 tons/yr Continuous release. Emission Days (days/year): 20 days/yr Fraction of EU tonnage used in region: 0.1 Fraction of Regional tonnage used Locally: 1 Maximum daily site tonnage (kg/d): 5000 kg / day Regional use tonnage (tonnes/year): 10000 tons/yr</p>
<p>Environmental factors not influenced by risk management Local freshwater dilution factor [EF1] 10 Local marine water dilution factor: [EF2] 100</p>
<p>Other given operational conditions affecting environmental exposure Release fraction to air from process (initial release prior to RMM): 1 Release fraction to soil from process (initial release prior to RMM): 0 Release fraction to wastewater from process (initial release prior to RMM): 0.0000001</p>
<p>Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.</p>
<p>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil If discharging to domestic sewage treatment plant, no onsite wastewater treatment required. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of =: >= 0 % Risk from environmental exposure is driven by Treat air emissions to provide a typical removal (or abatement?) efficiency of: 70 % Treat onsite wastewater (prior to receiving water discharge) to provide the required removal (or abatement) efficiency of =: >= 64.4 %</p>
<p>Organisation measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from wastewater. Sludge should be incinerated, contained or reclaimed.</p>
<p>Conditions and measures related to municipal sewage treatment plant Assumed domestic sewage treatment plant effluent flow is:[STP5] 2000 m3/day Estimated substance removal from wastewater via domestic sewage treatment is: 94.7 % Not applicable as there is no release to wastewater. The maximum allowable site tonnage (MSafe) based on domestic sewage plant effluent release is: 33000 kg / day Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs is: 94.7 %</p>
<p>Conditions and measures related to external treatment of waste for disposal External treatment and disposal of waste should comply with applicable local and/or national regulations [ETW3]</p>
<p>Conditions and measures related to external recovery of waste External recovery and recycling of waste should comply with applicable local and/or national regulations [ERW1]</p>
<p>Section 3 Exposure Estimation</p>
<p>3.1. Health</p>

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 30 of 40

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21]
3.2. Environment
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.[EE2]
Section 4 Guidance to check compliance with the Exposure Scenario
4.1. Health
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. [G32] Available hazard data do not support the need for a DNEL to be established for other health effects.[G36] Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. [G22] Risk Management Measures are based on qualitative risk characterisation. [G37] Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.[G23]
4.2. Environment
Further details on scaling and control technologies are provided in factsheet Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Section 1 Exposure Scenario Title	
Title:	
Lubricants - Industrial	
Use Descriptor	
Sector(s) of Use	SU3
Process Categories	PROC1, PROC10, PROC13, PROC17, PROC18, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9
Environmental Release Categories	ERC4, ERC7
Specific Environmental Release Category	ESVOC 1.1.v1 ,ESVOC 4.6a.v1
Processes, tasks, activities covered	
Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of machinery/engines and similar articles, reworking on reject articles, equipment maintenance and disposal of wastes.	
Section 2 Operational conditions and risk management measures	
Section 2.1 Control of worker exposure	
Product Characteristic	
Liquid	
Duration, frequency and amount	
Covers daily exposures up to 8 hours (unless stated differently)[G2] Covers percentage substance in the product up to 100 %[G13]	
Other given operational conditions affecting workers exposure	
Assumes a good basic standard of occupational hygiene is implemented [G1] Operation is carried out at elevated temperature (>20 C above ambient temperature)[OC7]	
Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions (only required controls to demonstrate safe use listed)	
General measures (Aspiration Hazard) The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting.	
General exposures (closed systems) PROC1 No other specific measures identified.	
General exposures (closed systems) PROC2 No other specific measures identified.	
General exposures (closed systems) PROC3 No other specific measures identified.	
General exposures (open systems) PROC4 No other specific measures identified.	
Bulk transfers Dedicated facility PROC8b No other specific measures identified.	
Filling / preparation of equipment from drums or containers Non-dedicated facility PROC8a No other specific measures identified.	
Initial factory fill of equipment PROC9 No other specific measures identified.	
Operation and lubrication of high energy open equipment PROC17 Provide extract ventilation to points where emissions occur.	
Manual Rolling, Brushing PROC10 No other specific measures identified.	

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 32 of 40

Treatment by dipping and pouring PROC13

No other specific measures identified.

Spraying PROC7

Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.

Maintenance (of larger plant items) and machine set up Dedicated facility Elevated temperature PROC8b

No other specific measures identified.

Maintenance of small items Non-dedicated facility PROC8a

No other specific measures identified.

Remanufacture of reject articles PROC9

No other specific measures identified.

Storage PROC1

Store substance within a closed system.

Storage PROC2

Store substance within a closed system.

Section 2.2 Control of environmental exposure

Product characteristics

Predominantly hydrophobic.
Substance is complex UVCB.

Duration, frequency and amount

Annual site tonnage (tonnes/year): 100 tons/yr
Continuous release.
Emission Days (days/year): 20 days/yr
Fraction of EU tonnage used in region: 0.1
Fraction of Regional tonnage used Locally: 1
Maximum daily site tonnage (kg/d): 5000 kg / day
Regional use tonnage (tonnes/year): 310000 tons/yr

Environmental factors not influenced by risk management

Local freshwater dilution factor [EF1] 10
Local marine water dilution factor: [EF2] 100

Other given operational conditions affecting environmental exposure

Release fraction to air from process (initial release prior to RMM): 0.0005
Release fraction to soil from process (initial release prior to RMM): 0.001
Release fraction to wastewater from process (initial release prior to RMM): 0.000001

Technical conditions and measures at process level (source) to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of =: >= 0 %
Risk from environmental exposure is driven by
Treat air emissions to provide a typical removal (or abatement?) efficiency of: 70 %
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal (or abatement) efficiency of =: >= 64.5 %

Organisation measures to prevent/limit release from site

Do not apply industrial sludge to natural soils.
Prevent discharge of undissolved substance to or recover from wastewater.
Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant

Assumed domestic sewage treatment plant effluent flow is:[STP5] 2000 m3/day
Estimated substance removal from wastewater via domestic sewage treatment is: 94.7 %
Not applicable as there is no release to wastewater.

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 33 of 40

The maximum allowable site tonnage (MSafe) based on domestic sewage plant effluent release is: 33000 kg / day
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs is: 94.7 %
Conditions and measures related to external treatment of waste for disposal
External treatment and disposal of waste should comply with applicable local and/or national regulations [ETW3]
Conditions and measures related to external recovery of waste
External recovery and recycling of waste should comply with applicable local and/or national regulations [ERW1]
Section 3 Exposure Estimation
3.1. Health
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21]
3.2. Environment
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.[EE2]
Section 4 Guidance to check compliance with the Exposure Scenario
4.1. Health
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. [G32]
Available hazard data do not support the need for a DNEL to be established for other health effects.[G36]
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. [G22]
Risk Management Measures are based on qualitative risk characterisation. [G37]
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.[G23]
4.2. Environment
Further details on scaling and control technologies are provided in factsheet
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
Scaled local assessments for EU refineries have been performed using site-specific data and are attached in PETRORISK file - 'Site-Specific Production' worksheet. [DSU6]

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 34 of 40

Section 1 Exposure Scenario Title	
Title:	
Metal working fluids / rolling oils - Industrial	
Use Descriptor	
Sector(s) of Use	SU3
Process Categories	PROC1, PROC10, PROC13, PROC17, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9
Environmental Release Categories	ERC4
Specific Environmental Release Category	ESVOC 1.1.v1 ,ESVOC 4.7a.v1
Processes, tasks, activities covered	
Covers the use in formulated MWFs (MWFs)/rolling oils including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils.	
Section 2 Operational conditions and risk management measures	
Section 2.1 Control of worker exposure	
Product Characteristic	
Liquid	
Duration, frequency and amount	
Covers daily exposures up to 8 hours (unless stated differently)[G2] Covers percentage substance in the product up to 100 %[G13]	
Other given operational conditions affecting workers exposure	
Assumes a good basic standard of occupational hygiene is implemented [G1] Operation is carried out at elevated temperature (>20 C above ambient temperature)[OC7]	
Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions (only required controls to demonstrate safe use listed)	
General measures (Aspiration Hazard) The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting.	
General exposures (closed systems) PROC1 No other specific measures identified.	
General exposures (closed systems) PROC2 No other specific measures identified.	
General exposures (closed systems) PROC3 No other specific measures identified.	
General exposures (open systems) PROC4 No other specific measures identified.	
Bulk transfers Dedicated facility PROC8b No other specific measures identified.	
Filling / preparation of equipment from drums or containers Dedicated facility PROC8b No other specific measures identified.	
Filling / preparation of equipment from drums or containers Dedicated facility PROC5 No other specific measures identified.	
Filling / preparation of equipment from drums or containers Dedicated facility PROC9 No other specific measures identified.	
Process sampling PROC3	

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 35 of 40

No other specific measures identified.

Metal machining operations PROC17

Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.

Treatment by dipping and pouring PROC13

No other specific measures identified.

Spraying PROC7

Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.

Manual Rolling, Brushing PROC10

No other specific measures identified.

Automated metal rolling/forming Use in contained systems Elevated temperature PROC2

No other specific measures identified.

Semi-automated metal rolling/forming Elevated temperature PROC17

Provide extract ventilation to points where emissions occur.

Semi-automated metal rolling/forming PROC4

No other specific measures identified.

Equipment cleaning and maintenance Dedicated facility PROC8b

Drain down system prior to equipment break-in or maintenance.

Equipment cleaning and maintenance Non-dedicated facility PROC8a

Drain down system prior to equipment break-in or maintenance.

Storage PROC1

Store substance within a closed system.

Storage PROC2

Store substance within a closed system.

Section 2.2 Control of environmental exposure

Product characteristics

Predominantly hydrophobic.

Substance is complex UVCB.

Duration, frequency and amount

Annual site tonnage (tonnes/year): 100 tons/yr

Continuous release.

Emission Days (days/year): 20 days/yr

Fraction of EU tonnage used in region: 0.1

Fraction of Regional tonnage used Locally: 1

Maximum daily site tonnage (kg/d): 5000 kg / day

Regional use tonnage (tonnes/year): 4200 tons/yr

Environmental factors not influenced by risk management

Local freshwater dilution factor [EF1] 10

Local marine water dilution factor: [EF2] 100

Other given operational conditions affecting environmental exposure

Release fraction to air from process (initial release prior to RMM): 0.02

Release fraction to soil from process (initial release prior to RMM): 0

Release fraction to wastewater from process (initial release prior to RMM): 0.000001

Technical conditions and measures at process level (source) to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of $\geq 0\%$

Risk from environmental exposure is driven by

Treat air emissions to provide a typical removal (or abatement?) efficiency of: 70 %

Treat onsite wastewater (prior to receiving water discharge) to provide the required removal (or abatement) efficiency

of =: >= 64.5 %
Organisation measures to prevent/limit release from site
Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from wastewater. Sludge should be incinerated, contained or reclaimed.
Conditions and measures related to municipal sewage treatment plant
Assumed domestic sewage treatment plant effluent flow is:[STP5] 2000 m ³ /day Estimated substance removal from wastewater via domestic sewage treatment is: 94.7 % Not applicable as there is no release to wastewater. The maximum allowable site tonnage (MSafe) based on domestic sewage plant effluent release is: 33000 kg / day Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs is: 94.7 %
Conditions and measures related to external treatment of waste for disposal
External treatment and disposal of waste should comply with applicable local and/or national regulations [ETW3]
Conditions and measures related to external recovery of waste
External recovery and recycling of waste should comply with applicable local and/or national regulations [ERW1]
Section 3 Exposure Estimation
3.1. Health
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21]
3.2. Environment
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.[EE2]
Section 4 Guidance to check compliance with the Exposure Scenario
4.1. Health
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. [G32] Available hazard data do not support the need for a DNEL to be established for other health effects.[G36] Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. [G22] Risk Management Measures are based on qualitative risk characterisation. [G37] Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.[G23]
4.2. Environment
Further details on scaling and control technologies are provided in factsheet Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 37 of 40

Section 1 Exposure Scenario Title	
Title:	
Lubricants - Professional (Low Release)	
Use Descriptor	
Sector(s) of Use	SU22
Process Categories	PROC1, PROC10, PROC11, PROC13, PROC17, PROC18, PROC2, PROC20, PROC3, PROC4, PROC8a, PROC8b, PROC9
Environmental Release Categories	ERC9A, ERC9B
Specific Environmental Release Category	ESVOC 1.1.v1 ,ESVOC 8.6c.v1 ,ESVOC 9.6b.v1
Processes, tasks, activities covered	
Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil.	
Section 2 Operational conditions and risk management measures	
Section 2.1 Control of worker exposure	
Product Characteristic	
Liquid	
Duration, frequency and amount	
Covers daily exposures up to 8 hours (unless stated differently)[G2] Covers percentage substance in the product up to 100 %[G13]	
Other given operational conditions affecting workers exposure	
Assumes a good basic standard of occupational hygiene is implemented [G1] Operation is carried out at elevated temperature (>20 C above ambient temperature)[OC7]	
Contributing Scenarios/ Specific Risk Management Measures and Operating Conditions (only required controls to demonstrate safe use listed)	
General measures (Aspiration Hazard) The H304 risk phrase (May be fatal if swallowed and enters airways) relates to potential for aspiration, a non-quantifiable hazard determined by physico-chemical properties (i.e. viscosity) that can occur during ingestion and also if it is vomited following ingestion. A DNEL cannot be derived. Risks from the physicochemical hazards of substances can be controlled by implementing risk management measures. For substances classified as H304, the following measures need to be implemented to control the aspiration hazard. Do not ingest. If swallowed then seek immediate medical attention. Do NOT induce vomiting.	
General exposures (closed systems) PROC1 No other specific measures identified.	
General exposures (closed systems) PROC2 No other specific measures identified.	
General exposures (closed systems) PROC3 No other specific measures identified.	
Operation of equipment containing engine oils and similar (closed systems) PROC20 No other specific measures identified.	
General exposures (open systems) PROC4 No other specific measures identified.	
Bulk transfers Dedicated facility PROC8b No other specific measures identified.	
Filling / preparation of equipment from drums or containers Dedicated facility PROC8b No other specific measures identified.	
Filling / preparation of equipment from drums or containers Non-dedicated facility PROC8a Avoid carrying out activities involving exposure for more than 1 hour.	
Operation and lubrication of high energy open equipment Indoor PROC17	

Product Name: VISOM 4
 Revision Date: 11 Dec 2019
 Page 38 of 40

Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.

Operation and lubrication of high energy open equipment Indoor PROC18

Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.

Operation and lubrication of high energy open equipment Outdoor. PROC17

Ensure operation is undertaken outdoors.

Avoid carrying out operation for more than 4 hours.

Limit the substance content in the mixture to 25 %.

Maintenance (of larger plant items) and machine set up Dedicated facility Elevated temperature PROC8b

Drain down system prior to equipment break-in or maintenance.

Provide extract ventilation to emission points when contact with warm (> 50°C) lubricant is likely.

Maintenance of small items Non-dedicated facility Elevated temperature PROC8a

Drain or remove substance from equipment prior to break-in or maintenance.

provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Engine lubricant service PROC9

No other specific measures identified.

Manual Rolling, Brushing PROC10

No other specific measures identified.

Spraying PROC11

Carry out in a vented booth or extracted enclosure.

or

Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.

Avoid carrying out activities involving exposure for more than 1 hour.

OR

Wear a respirator conforming to EN140 with Type A filter or better.

Treatment by dipping and pouring PROC13

No other specific measures identified.

Storage PROC1

Store substance within a closed system.

Section 2.2 Control of environmental exposure

Product characteristics

Predominantly hydrophobic.

Substance is complex UVCB.

Duration, frequency and amount

Annual site tonnage (tonnes/year): 53 tons/yr

Continuous release.

Emission Days (days/year): 365 days/yr

Fraction of EU tonnage used in region: 0.1

Fraction of Regional tonnage used Locally: 1

Maximum daily site tonnage (kg/d): 365 kg / day

Regional use tonnage (tonnes/year): 110000 tons/yr

Environmental factors not influenced by risk management

Local freshwater dilution factor [EF1] 10

Local marine water dilution factor: [EF2] 100

Other given operational conditions affecting environmental exposure

Release fraction to air from wide dispersive use (regional only): 0.01

Release fraction to soil from wide dispersive use (regional only): 0.01

Release fraction to wastewater from wide dispersive use: 0.01

Technical conditions and measures at process level (source) to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

Product Name: VISOM 4

Revision Date: 11 Dec 2019

Page 39 of 40

<p>If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of $\geq 0\%$</p> <p>Risk from environmental exposure is driven by</p> <p>Treat air emissions to provide a typical removal (or abatement?) efficiency of: Not Applicable</p> <p>Treat onsite wastewater (prior to receiving water discharge) to provide the required removal (or abatement) efficiency of $\geq 76.1\%$</p>
<p>Organisation measures to prevent/limit release from site</p> <p>Do not apply industrial sludge to natural soils.</p> <p>Sludge should be incinerated, contained or reclaimed.</p>
<p>Conditions and measures related to municipal sewage treatment plant</p> <p>Assumed domestic sewage treatment plant effluent flow is:[STP5] 2000 m³/day</p> <p>Estimated substance removal from wastewater via domestic sewage treatment is: 94.7 %</p> <p>Not applicable as there is no release to wastewater.</p> <p>The maximum allowable site tonnage (MSafe) based on domestic sewage plant effluent release is: 650 kg / day</p> <p>Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs is: 94.7 %</p>
<p>Conditions and measures related to external treatment of waste for disposal</p> <p>External treatment and disposal of waste should comply with applicable local and/or national regulations [ETW3]</p>
<p>Conditions and measures related to external recovery of waste</p> <p>External recovery and recycling of waste should comply with applicable local and/or national regulations [ERW1]</p>
<p>Section 3 Exposure Estimation</p>
<p>3.1. Health</p> <p>The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21]</p>
<p>3.2. Environment</p> <p>The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.[EE2]</p>
<p>Section 4 Guidance to check compliance with the Exposure Scenario</p>
<p>4.1. Health</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. [G32]</p> <p>Available hazard data do not support the need for a DNEL to be established for other health effects.[G36]</p> <p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. [G22]</p> <p>Risk Management Measures are based on qualitative risk characterisation. [G37]</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.[G23]</p>
<p>4.2. Environment</p> <p>Further details on scaling and control technologies are provided in factsheet</p> <p>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</p> <p>Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.</p> <p>Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.</p>

Product Name: VISOM 4
Revision Date: 11 Dec 2019
Page 40 of 40
