

Product Name: MOBIL COOLANT READY MIXED -36 C
Revision Date: 21 Nov 2018
Page 1 of 12

SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: MOBIL COOLANT READY MIXED -36 C
Product Description: Glycol
Product Code: 331058, 351010602010
Intended Use: Antifreeze/coolant

COMPANY IDENTIFICATION

Manufacturer/Supplier:
For details contact ExxonMobil International LLC
Taiwan Branch
6th Flr., No 2, Tun Hua South Road
IBM Building, Section 1
Taipei Taiwan

24 Hour Health Emergency	00801-863-136 (8:30 am - 16:30 pm) Mon-Fri
Supplier General Contact	886-2-2734-6888
FAX	886-2-2734-6999

SECTION 2 HAZARDS IDENTIFICATION

This material is hazardous according to regulatory guidelines (see (M)SDS Section 15).

CLASSIFICATION:

Acute oral toxicant: Category 4. Specific target organ toxicant (repeated exposure): Category 2.

LABEL:

Symbol:



Signal Word: Warning

Hazard Statements:

Product Name: MOBIL COOLANT READY MIXED -36 C

Revision Date: 21 Nov 2018

Page 2 of 12

Health: H302: Harmful if swallowed. H373: May cause damage to organs through prolonged or repeated exposure. Kidney

Precautionary Statements:

General: P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use.

Prevention: P260: Do not breathe mist / vapours. P264: Wash skin thoroughly after handling. P270: Do not eat, drink or smoke when using this product.

Response: P301 + P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P314: Get medical advice/attention if you feel unwell. P330: Rinse mouth.

Disposal: P501: Dispose of contents and container in accordance with local regulations.

Contains: ETHYLENE GLYCOL

Other hazard information:

PHYSICAL / CHEMICAL HAZARDS

No significant hazards.

HEALTH HAZARDS

High-pressure injection under skin may cause serious damage. Ingestion may cause serious adverse effects and may be fatal. May cause kidney failure and central nervous system effects. Prolonged exposure to elevated concentrations of mist or liquid may cause irritation of the skin, eyes, and respiratory tract.

ENVIRONMENTAL HAZARDS

No significant hazards.

NOTE: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

SECTION 3	COMPOSITION / INFORMATION ON INGREDIENTS
------------------	---

This material is defined as a mixture.

Hazardous Substance(s) or Complex Substance(s) required for disclosure

Name	CAS#	Concentration*	GHS Hazard Codes
DISODIUM TETRABORATE PENTAHYDRATE	12179-04-3	0.5 - 1.3%	H319(2A), H360(1B)(D), H360(1B)(F)
ETHYLENE GLYCOL	107-21-1	50 - < 60%	H302, H373

Product Name: MOBIL COOLANT READY MIXED -36 C

Revision Date: 21 Nov 2018

Page 3 of 12

TCSCA: Toxic Chemical Substances: None.

* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

SECTION 4

FIRST AID MEASURES

INHALATION

Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device.

SKIN CONTACT

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

Seek immediate medical attention.

NOTE TO PHYSICIAN

This product contains ethylene glycol and/or diethylene glycol which, if ingested, are metabolized to toxic metabolites by the enzyme alcohol dehydrogenase, for which ethanol and 4-methylpyrazole {U.S. drug name Fomepizole, trade name Antizol} are antagonists. Administration of oral or intravenous ethanol or intravenous 4-methylpyrazole may arrest further metabolism of this material and thereby ameliorate the toxicity. Use of ethanol or 4-methylpyrazole does not affect toxic metabolites that are already present and is not a substitute for hemodialysis.

SECTION 5

FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, alcohol-resistant foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Inappropriate Extinguishing Media: Straight Streams of Water or Regular Foam

Product Name: MOBIL COOLANT READY MIXED -36 C

Revision Date: 21 Nov 2018

Page 4 of 12

FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Unusual Fire Hazards: Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

Hazardous Combustion Products: Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume

FLAMMABILITY PROPERTIES

Flash Point [Method]: 111 C (232 F) [ASTM D-93]

Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D

Autoignition Temperature: N/D

SECTION 6	ACCIDENTAL RELEASE MEASURES
-----------	-----------------------------

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

SPILL MANAGEMENT

Land Spill: Stop leak if you can do it without risk. Do not touch or walk through spilled material. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Water Spill: Stop leak if you can do it without risk. This product emulsifies, disperses or is miscible in water. Remove material, as much as possible, using mechanical equipment.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For

Product Name: MOBIL COOLANT READY MIXED -36 C

Revision Date: 21 Nov 2018

Page 5 of 12

this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Remove debris in path of spill and remove contaminated debris from shoreline and water surface and dispose of according to local regulations. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

SECTION 7	HANDLING AND STORAGE
------------------	-----------------------------

HANDLING

Avoid breathing mists or vapors. Avoid contact with skin. Prevent small spills and leakage to avoid slip hazard.

Static Accumulator: This material is not a static accumulator.

STORAGE

Do not store in open or unlabelled containers.

SECTION 8	EXPOSURE CONTROLS / PERSONAL PROTECTION
------------------	--

EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name	Form	Limit / Standard	Note	Source	Year
DISODIUM TETRABORATE PENTAHYDRATE	Inhalable fraction	STEL 6 mg/m ³		ACGIH	2018
DISODIUM TETRABORATE PENTAHYDRATE	Inhalable fraction	TWA 2 mg/m ³		ACGIH	2018
ETHYLENE GLYCOL	Vapor.	Ceiling 127 mg/m ³	50 ppm	Taiwan PELs	2018
ETHYLENE GLYCOL	Mist.	STEL 15 mg/m ³		Taiwan PELs	2018
ETHYLENE GLYCOL	Mist.	TWA 10 mg/m ³		Taiwan PELs	2018
ETHYLENE GLYCOL	Aerosol, inhalable	STEL 10 mg/m ³		ACGIH	2018

Product Name: MOBIL COOLANT READY MIXED -36 C

Revision Date: 21 Nov 2018

Page 6 of 12

ETHYLENE GLYCOL	Vapor fraction	STEL	50 ppm			ACGIH	2018
ETHYLENE GLYCOL	Vapor fraction	TWA	25 ppm			ACGIH	2018

Biological limits

No biological limits allocated.

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No protection is ordinarily required under normal conditions of use and with adequate ventilation. Particulate

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

If prolonged or repeated contact is likely, chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves. Nitrile, Viton

Product Name: MOBIL COOLANT READY MIXED -36 C

Revision Date: 21 Nov 2018

Page 7 of 12

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:
If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9	PHYSICAL AND CHEMICAL PROPERTIES
-----------	----------------------------------

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

GENERAL INFORMATION

Physical State: Liquid
Color: Blue-Green
Odor: Odorless
Odor Threshold: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 20 C): 1.07
Flammability (Solid, Gas): N/A
Flash Point [Method]: 111 C (232 F) [ASTM D-93]
Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D
Autoignition Temperature: N/D
Boiling Point / Range: N/D
Decomposition Temperature: N/D
Vapor Density (Air = 1): N/D
Vapor Pressure: N/D
Evaporation Rate (n-butyl acetate = 1): N/D
pH: N/D
Log Pow (n-Octanol/Water Partition Coefficient): N/D
Solubility in Water: Complete
Viscosity: [N/D at 40 C]
Oxidizing Properties: See Hazards Identification Section.

Product Name: MOBIL COOLANT READY MIXED -36 C
 Revision Date: 21 Nov 2018
 Page 8 of 12

OTHER INFORMATION

Freezing Point: N/D
Melting Point: N/D

SECTION 10	STABILITY AND REACTIVITY
-------------------	---------------------------------

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: Excessive heat. High energy sources of ignition.

MATERIALS TO AVOID: Strong Acids, Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization will not occur.

SECTION 11	TOXICOLOGICAL INFORMATION
-------------------	----------------------------------

INFORMATION ON TOXICOLOGICAL EFFECTS

<u>Hazard Class</u>	<u>Conclusion / Remarks</u>
Inhalation	
Acute Toxicity: No end point data for material.	Minimally Toxic. Base on assessment of the components.
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
Ingestion	
Acute Toxicity (Human): LDLo 100 ml	Moderately toxic. Base on assessment of the components.
Skin	
Acute Toxicity: No end point data for material.	Minimally Toxic. Base on assessment of the components.
Skin Corrosion/Irritation: No end point data for material.	Negligible irritation to skin at ambient temperatures. Base on assessment of the components.
Eye	
Serious Eye Damage/Irritation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Base on assessment of the components.
Sensitization	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: No end point data for material.	Not expected to be a skin sensitizer. Base on assessment of the components.
Aspiration: No end point data for material.	Not expected to be an aspiration hazard. Based on physico-chemical properties of the material.
Germ Cell Mutagenicity: No end point data for material.	Not expected to be a germ cell mutagen. Base on assessment of the components.

Product Name: MOBIL COOLANT READY MIXED -36 C

Revision Date: 21 Nov 2018

Page 9 of 12

Carcinogenicity: No end point data for material.	Not expected to cause cancer. Base on assessment of the components.
Reproductive Toxicity: No end point data for material.	Not expected to be a reproductive toxicant. Base on assessment of the components.
Lactation: No end point data for material.	Not expected to cause harm to breast-fed children.
Specific Target Organ Toxicity (STOT)	
Single Exposure: No end point data for material.	Not expected to cause organ damage from a single exposure.
Repeated Exposure: No end point data for material.	Concentrated, prolonged or deliberate exposure may cause organ damage. Base on assessment of the components.

TOXICITY FOR SUBSTANCES

NAME	ACUTE TOXICITY
ETHYLENE GLYCOL	Oral Lethality: LD50 4700 mg/kg (Rat)

OTHER INFORMATION

For the product itself:

Target Organs Repeated Exposure: Kidney

Contains:

ETHYLENE GLYCOL (EG): Repeated high oral exposure has caused kidney damage, neurological effects, degeneration of the liver and changes in blood chemistry and circulating blood cells in laboratory animals. Repeated overexposure has the potential to cause similar toxic effects in humans. EG causes developmental and reproductive effects at high dose levels in laboratory animals. The relevance of these findings to humans is uncertain.

Sodium tetraborate: Adverse effects on fertility and fetal development have been observed in laboratory animals.

IARC Classification:

The following ingredients are cited on the lists below: None.

--REGULATORY LISTS SEARCHED--

1 = IARC 1

2 = IARC 2A

3 = IARC 2B

SECTION 12

ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar

materials, through the application of bridging principals.

ECOTOXICITY

Material -- Not expected to be harmful to aquatic organisms.

MOBILITY

Material -- Expected to remain in water or migrate through soil.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Material -- Expected to be readily biodegradable.

Atmospheric Oxidation:

Material -- Expected to degrade rapidly in air

BIOACCUMULATION POTENTIAL

Material -- Potential to bioaccumulate is low.

SECTION 13

DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

DISPOSAL RECOMMENDATIONS

Even though this product is biodegradable, it must not be indiscriminately discarded into the environment. Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14

TRANSPORT INFORMATION

LAND (ADR) : Not Regulated for Land Transport

Product Name: MOBIL COOLANT READY MIXED -36 C
Revision Date: 21 Nov 2018
Page 11 of 12

SEA (IMDG): Not Regulated for Sea Transport according to IMDG-Code

Marine Pollutant: No

AIR (IATA): Not Regulated for Air Transport
, EHS

SECTION 15

REGULATORY INFORMATION

This material is considered hazardous according to The Regulations on Labelling and Hazard Communications for Hazardous Materials.

REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS

Toxic Chemical Substances Control Act (TCSCA): Not Regulated

Listed or exempt from listing/notification on the following chemical inventories (May contain substance(s) subject to notification to the EPA Active TSCA inventory prior to import to USA):
AICS, DSL, ENCS, IECSC, KECI, PICCS, TCSI, TSCA

SECTION 16

OTHER INFORMATION

N/D = Not determined, N/A = Not applicable

KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

H302: Harmful if swallowed; Acute Tox Oral, Cat 4

H319(2A): Causes serious eye irritation; Serious Eye Damage/Irr, Cat 2A

H360(1B)(D): May damage the unborn child; Repro Tox, Cat 1B (Develop)

H360(1B)(F): May damage fertility; Repro Tox, Cat 1B (Fertility)

H373: May cause damage to organs through prolonged or repeated exposure; Target Organ, Repeated, Cat 2

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

GHS Target Organ List information was added.

GHS Target Organ List information was deleted.

Section 01: Company Contact Methods information was modified.

Section 08: Exposure Limits Table information was modified.

Section 12: information was modified.



Product Name: MOBIL COOLANT READY MIXED -36 C

Revision Date: 21 Nov 2018

Page 12 of 12

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

DGN: 7078548XTW (551457)

