

# SAFETY DATA SHEET

## SECTION 1 IDENTIFICATION OF THE HAZARDOUS CHEMICAL AND OF THE SUPPLIER

As of the revision date above, this SDS meets the regulations in Malaysia.

### PRODUCT IDENTIFIER

**Product Name:** MOBIL ATF LT 71141  
**Product Description:** Base Oil and Additives  
**Product Code:** 201530202037, 520882-60

### RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE

**Recommended Use:** Automatic gearbox fluid  
**Restrictions on Use:** This product is not recommended for any industrial, professional or consumer use other than the Recommended Uses above.

### SUPPLIER DETAILS

**Supplier:** ExxonMobil Asia Pacific Pte.Ltd. (Company No.: 196800312N)  
1 Harbour Front Place  
#06-00 Harbour Front Tower One 098633 Singapore

**24 Hour Emergency Telephone** 1-800-815-308 / +1-703-527-3887

**Supplier General Contact** (+65) 6885 8000

**Supplier:** HT LUBRICANT SENDIRIAN BERHAD (646137-M)  
90, Jin Tampoi  
Johor Bahru 81200 Malaysia

**Supplier General Contact** +607-335 3663

**Supplier:** MOBILUB TRADING SENDIRIAN BERHAD (514125-H)  
No.1, Jalan Meranti Puchong,  
D'25@Meranti Puchong  
Selangor Darul Ehsan 47120 Malaysia

**Supplier General Contact** +603-8066 5081

**Supplier:** OPTIMUM FLUIDS MARKETING SENDIRIAN BERHAD (668909-D)  
Plot 110, Lrg Perindustrian Bukit Minyak 11  
Kws Perindustrian Bukit Minyak  
Penang 14100 BM Malaysia

**Supplier General Contact** +604-510 2166

**Supplier:** TIMUR LUBE SDN. BHD. (806793-H)  
Wisma Hubline, 1st Floor, Lease No.3815, Lot 10914, Section 64

Product Name: MOBIL ATF LT 71141  
Revision Date: 12 Aug 2020  
Page 2 of 12

---

KTLD, Jalan Datuk Abang Abdul Rahim  
93450 Kuching  
Sarawak Malaysia

**Supplier General Contact**

+6082 257567

## SECTION 2 HAZARDS IDENTIFICATION

This material is hazardous according to regulatory guidelines (see SDS Section 15).

### CLASSIFICATION:

Chronic aquatic toxicant: Category 3.

### LABEL ELEMENTS:

**Symbol:** No Symbol

**Signal Word:** No Signal Word

### Hazard Statements:

Environmental: H412: Harmful to aquatic life with long lasting effects.

### Precautionary Statements:

Prevention: P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P273: Avoid release to the environment. P281: Use personal protective equipment as required.

Response: P308 + P313: IF exposed or concerned: Get medical advice/attention.

Storage: P405: Store locked up.

Disposal: P501: Dispose of contents and container in accordance with local regulations.

### Other hazard information:

### PHYSICAL / CHEMICAL HAZARDS

No significant hazards.

### HEALTH HAZARDS

High-pressure injection under skin may cause serious damage. Excessive exposure may result in eye, skin, or respiratory irritation.

### ENVIRONMENTAL HAZARDS

No additional hazards.

**NOTE:** This material should not be used for any other purpose than the recommended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

Product Name: MOBIL ATF LT 71141  
 Revision Date: 12 Aug 2020  
 Page 3 of 12

**SECTION 3 COMPOSITION AND INFORMATION OF THE INGREDIENTS OF THE HAZARDOUS CHEMICAL**

This material is defined as a mixture.

**Hazardous Substance(s) or Complex Substance(s) required for disclosure**

Name	CAS#	Concentration*	GHS Hazard Codes
ALKYL ALKOXY AMINE		0.025 - < 0.1%	H302, H314(1B), H400(M factor 100), H410(M factor 1)
BIS (2-HYDROXYETHYL) COCOALKYLAMINE	61791-31-9	< 0.25%	H302, H361(D), H314(1C), H400(M factor 10), H410(M factor 10)
BIS(2-HYDROXYETHYL) TALLOW AMINE	61791-44-4	0.1 - < 0.25%	H302, H314(1C), H400(M factor 10), H410(M factor 1)
SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE	64742-54-7	50 - < 60%	H304
SOLVENT DEWAXED HEAVY PARAFFINIC DISTILLATE	64742-65-0	5 - < 10%	H304
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC	64742-94-5	0.1 - < 1%	[H227], H304, H336, H351, [H401], H411

Note - any hazard code in brackets [Hxxx] is a GHS building block that was not adopted by Malaysia in the CLASS Regulation and therefore is not applicable in Malaysia and is shown for informational purposes only.

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**SECTION 4 FIRST AID MEASURES**

**INHALATION**

Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device.

**SKIN CONTACT**

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

**EYE CONTACT**

Flush thoroughly with water. If irritation occurs, get medical assistance.

**INGESTION**

Seek immediate medical attention.

**NOTE TO PHYSICIAN**

None

**SECTION 5 FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA**

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

---

**Inappropriate Extinguishing Media:** Straight streams of water

## FIRE FIGHTING

**Fire Fighting Instructions:** Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Hazardous Combustion Products:** Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulphur oxides

## FLAMMABILITY PROPERTIES

**Flash Point [Method]:** >180°C (356°F) [ASTM D-92]

**Flammable Limits (Approximate volume % in air):** LEL: 0.9 UEL: 7.0

**Autoignition Temperature:** N/D

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

### PROTECTIVE MEASURES

Avoid contact with spilled material. See Section 6 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 5 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

For emergency responders: Respiratory protection: respiratory protection will be necessary only in special cases, e.g., formation of mists. Half-face or full-face respirator with filter(s) for dust/organic vapor or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to hydrocarbons are recommended. Gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

### ENVIRONMENTAL PRECAUTIONS

Large Spills: Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

### METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

**Land Spill:** Stop leak if you can do so without risk. Recover by pumping or with suitable absorbent.

**Water Spill:** Stop leak if you can do so without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

## SECTION 7 HANDLING AND STORAGE

### PRECAUTIONS FOR SAFE HANDLING

Avoid all personal contact. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or earthing procedures. However, bonding and earthing may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

**Static Accumulator:** This material is a static accumulator.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

### CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

The type of container used to store the material may affect static accumulation and dissipation. Do not store in open or unlabelled containers. Keep away from incompatible materials.

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### CONTROL PARAMETERS

### EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name	Form	Limit/Standard			Note	Source
SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE	Mist.	PEL	5 mg/m <sup>3</sup>			Malaysia PEL
SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE	Inhalable fraction.	TWA	5 mg/m <sup>3</sup>			ACGIH
SOLVENT DEWAXED HEAVY PARAFFINIC DISTILLATE	Mist.	PEL	5 mg/m <sup>3</sup>			Malaysia PEL
SOLVENT DEWAXED HEAVY PARAFFINIC DISTILLATE	Inhalable fraction.	TWA	5 mg/m <sup>3</sup>			ACGIH

**Exposure limits/standards for materials that can be formed when handling this product:** When mists/aerosols can occur the following is recommended: 5 mg/m<sup>3</sup> - ACGIH TLV (inhalable fraction).

---

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

### Biological limits

No biological limits allocated.

### ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:  
No special requirements under ordinary conditions of use and with adequate ventilation.

### PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:  
No special requirements under ordinary conditions of use and with adequate ventilation.  
Particulate

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:  
Chemical resistant gloves are recommended. Nitrile, Viton

**Eye Protection:** If contact is likely, safety glasses with side shields are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:  
Chemical/oil resistant clothing is recommended.

### ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

Product Name: MOBIL ATF LT 71141  
 Revision Date: 12 Aug 2020  
 Page 7 of 12

**Note:** Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

## GENERAL INFORMATION

**Physical State:** Liquid  
**Colour:** Amber  
**Odour:** Characteristic  
**Odour Threshold:** N/D

## IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

**Relative Density (at 15 °C):** 0.855 [ASTM D4052]  
**Flammability (Solid, Gas):** N/A  
**Flash Point [Method]:** >180°C (356°F) [ASTM D-92]  
**Flammable Limits (Approximate volume % in air):** LEL: 0.9 UEL: 7.0  
**Autoignition Temperature:** N/D  
**Boiling Point / Range:** > 316°C (600°F) [Estimated]  
**Decomposition Temperature:** N/D  
**Vapour Density (Air = 1):** > 2 at 101 kPa  
**Vapour Pressure:** < 0.013 kPa (0.1 mm Hg) at 20 °C [Estimated]  
**Evaporation Rate (n-butyl acetate = 1):** N/D  
**pH:** N/A  
**Log Pow (n-Octanol/Water Partition Coefficient):** > 3.5  
**Solubility in Water:** Negligible  
**Viscosity:** 40 cSt (40 mm<sup>2</sup>/sec) at 40°C | 7 cSt (7 mm<sup>2</sup>/sec) at 100°C [ASTM D 445]  
**Oxidizing Properties:** See Hazards Identification Section.

## OTHER INFORMATION

**Freezing Point:** N/D  
**Melting Point:** N/A  
**Pour Point:** -48°C (-54°F) [ASTM D97]  
**DMSO Extract (mineral oil only), IP-346:** < 3 %wt

## SECTION 10 STABILITY AND REACTIVITY

**REACTIVITY:** See sub-sections below.

**STABILITY:** Material is stable under normal conditions.

**CONDITIONS TO AVOID:** Excessive heat. High energy sources of ignition.

**INCOMPATIBLE MATERIALS:** Strong oxidisers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.

## SECTION 11 TOXICOLOGICAL INFORMATION

### INFORMATION ON TOXICOLOGICAL EFFECTS

Hazard Class	Conclusion / Remarks
--------------	----------------------

Product Name: MOBIL ATF LT 71141

Revision Date: 12 Aug 2020

Page 8 of 12

<b>Inhalation</b>	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
<b>Ingestion</b>	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
<b>Skin</b>	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin Corrosion/Irritation: No end point data for material.	Negligible irritation to skin at ambient temperatures. Based on assessment of the components.
<b>Eye</b>	
Serious Eye Damage/Irritation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.
<b>Sensitisation</b>	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: No end point data for material.	Not expected to be a skin sensitizer. Based on assessment of the components.
<b>Aspiration:</b> Data available.	Not expected to be an aspiration hazard. Based on physico-chemical properties of the material.
<b>Germ Cell Mutagenicity:</b> No end point data for material.	Not expected to be a germ cell mutagen. Based on assessment of the components.
<b>Carcinogenicity:</b> No end point data for material.	Contains a substance that may cause cancer. Based on assessment of the components.
<b>Reproductive Toxicity:</b> No end point data for material.	Contains a substance that may be a reproductive toxicant. Based on assessment of the components.
<b>Lactation:</b> No end point data for material.	Not expected to cause harm to breast-fed children.
<b>Specific Target Organ Toxicity (STOT)</b>	
Single Exposure: No end point data for material.	Not expected to cause organ damage from a single exposure.
Repeated Exposure: No end point data for material.	Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components.

## TOXICITY FOR SUBSTANCES

NAME	ACUTE TOXICITY
BIS (2-HYDROXYETHYL) COCOALKYLAMINE	Oral Lethality: LD 50 1500 mg/kg (Rat)

## OTHER INFORMATION

### Contains:

Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitising in test animals.

### IARC Classification:

The following ingredients are cited on the lists below: None.



Product Name: MOBIL ATF LT 71141  
Revision Date: 12 Aug 2020  
Page 9 of 12

--REGULATORY LISTS SEARCHED--

1 = IARC 1

2 = IARC 2A

3 = IARC 2B

**SECTION 12 ECOLOGICAL INFORMATION**

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

**ECOTOXICITY**

Material -- Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

**MOBILITY IN SOIL**

Base oil component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

**PERSISTENCE AND DEGRADABILITY**

**Biodegradation:**

Base oil component -- Expected to be inherently biodegradable

**BIOACCUMULATIVE POTENTIAL**

Base oil component -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

**OTHER ADVERSE EFFECTS**

No adverse effects are expected.

**SECTION 13 DISPOSAL INFORMATION**

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

**DISPOSAL METHODS**

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Protect the environment. Dispose of used oil at designated sites. Minimize skin contact. Do not mix used oils with solvents, brake fluids or coolants.

**REGULATORY DISPOSAL INFORMATION**

**Environmental Quality (Scheduled Wastes) Regulations 2005 waste code:** SW 305

Note: These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste disposal code(s); This material is considered as hazardous waste pursuant to Environmental Quality (Scheduled Wastes) Regulations 2005.

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue

Product Name: MOBIL ATF LT 71141  
 Revision Date: 12 Aug 2020  
 Page 10 of 12

and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

## SECTION 14 TRANSPORT INFORMATION

**LAND :** Not Regulated for Land Transport

**SEA (IMDG):** Not Regulated for Sea Transport according to IMDG-Code

**Marine Pollutant:** No

**AIR (IATA):** Not Regulated for Air Transport

## SECTION 15 REGULATORY INFORMATION

This material is hazardous as defined by the Occupational Safety and Health (Classification, Labeling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

### REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS

Listed or exempt from listing/notification on the following chemical inventories (May contain substance(s) subject to notification to the EPA Active TSCA inventory prior to import to USA): AIIC, DSL, IECSC, ISHL, KECI, TCSI, TSCA

**Special Cases:**

Inventory	Status
PICCS	Restrictions Apply

**National Laws and Regulations:**

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000  
 Occupational Safety and Health (Control of Industrial Major Accident Hazards) Regulation 1996

## SECTION 16 OTHER INFORMATION

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

Acronym	Full text
N/A	Not applicable
N/D	Not determined
NE	Not established
VOC	Volatile Organic Compound
AIIC	Australian Inventory of Industrial Chemicals
AIHA WEEL	American Industrial Hygiene Association Workplace Environmental Exposure Limits

Product Name: MOBIL ATF LT 71141

Revision Date: 12 Aug 2020

Page 11 of 12

---

ASTM	ASTM International, originally known as the American Society for Testing and Materials (ASTM)
DSL	Domestic Substance List (Canada)
EINECS	European Inventory of Existing Commercial Substances
ELINCS	European List of Notified Chemical Substances
ENCS	Existing and new Chemical Substances (Japanese inventory)
IECSC	Inventory of Existing Chemical Substances in China
KECI	Korean Existing Chemicals Inventory
NDSL	Non-Domestic Substances List (Canada)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances
TLV	Threshold Limit Value (American Conference of Governmental Industrial Hygienists)
TSCA	Toxic Substances Control Act (U.S. inventory)
UVCB	Substances of Unknown or Variable composition, Complex reaction products or Biological materials
LC	Lethal Concentration
LD	Lethal Dose
LL	Lethal Loading
EC	Effective Concentration
EL	Effective Loading
NOEC	No Observable Effect Concentration
NOELR	No Observable Effect Loading Rate

**KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):**

H227: Combustible liquid; Flammable Liquid, Cat 4  
H302: Harmful if swallowed; Acute Tox Oral, Cat 4  
H304: May be fatal if swallowed and enters airways; Aspiration, Cat 1  
H314(1B): Causes severe skin burns and eye damage; Skin Corr/Irritation, Cat 1B  
H314(1C): Causes severe skin burns and eye damage; Skin Corr/Irritation, Cat 1C  
H318: Causes serious eye damage; Serious Eye Damage/Irr, Cat 1  
H336: May cause drowsiness or dizziness; Target Organ Single, Narcotic  
H351: Suspected of causing cancer; GHS Carcinogenicity, Cat 2  
H361(D): Suspected of damaging the unborn child; Repro Tox, Cat 2 (Develop)  
H400: Very toxic to aquatic life; Acute Env Tox, Cat 1  
H401: Toxic to aquatic life; Acute Env Tox, Cat 2  
H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1  
H411: Toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 2

**THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**

Section 05: First Aid Ingestion information was modified.  
Section 15: National Chemical Inventory Listing information was modified.  
TIMUR LUBE SDN. BHD. (806793-H): Section 01: Supplier Mailing Address information was modified.

---

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

Product Name: MOBIL ATF LT 71141  
Revision Date: 12 Aug 2020  
Page 12 of 12

---

DGN: 7096064XMY (547095)

---