

Product Name: MOBILITH SHC PM 460 Revision Date: 15 Jul 2021 Page 1 of 11

# SAFETY DATA SHEET

# SECTION 1 IDENTIFICATION OF THE HAZARDOUS CHEMICAL AND OF THE SUPPLIER

PRODUCT IDENTIFIER	BILITH SHC PM 460 Synthetic Base Stocks and 2015A0204068, 643940	Additives	lations in Malaysia.
RECOMMENDED USE OF THE Recommended Use: Restrictions on Use	E CHEMICAL AND RESTRICT Grease None unless specified elsewho		
SUPPLIER DETAILS Supplier:	ExxonMobil Asia Pacific Pte.Lto 1 Harbour Front Place #06-00 Harbour Front Tower One	d. (Company No	
24 Hour Emergency Tele	ephone	1-800-815-30	8 / +1-703-527-3887
Supplier General Conta	ct	(+65) 6885 80	000
Supplier:	<b>HT LUBRICANT SE</b> 90, Jin Tampoi Johor Bahru 81	NDIRIAN BERH	
Supplier General Contact FAX		+607-335 3663 +607-335 8603	
Supplier:	<b>MOBILUB TRADIN</b> No.1, Jalan Meranti D'25@Meranti Puch Selangor Darul Ehs	Puchong, long	<b>ERHAD (514125-H)</b> Malaysia
Supplier General Contact FAX	-	+603-8066 508 +603-8066 508	1
Supplier:	<b>OPTIMUM FLUIDS</b> PLOT 110, LGR.PE KAW.PENINDUSTF Penang 14100	RINDUSTRIAN, RIAN, Bukit Merta	
Supplier General Contact		+604-510 2166	



Product Name: MOBILITH SHC PM 460 Revision Date: 15 Jul 2021 Page 2 of 11

#### Supplier:

# TIMUR LUBE SDN. BHD. (806793-H)

Wisma Hubline,1st Floor, Lease No.3815, Lot 10914, Section 64 KTLD, Jalan Datuk Abang Abdul Rahim 93450 Kuching Sarawak Malaysia

**Supplier General Contact** 

+6 082 338567

# SECTION 2 HAZARDS IDENTIFICATION

This material is not hazardous according to regulatory guidelines (see SDS Section 15).

# Other hazard information:

# PHYSICAL / CHEMICAL HAZARDS

No significant hazards.

### **HEALTH HAZARDS**

High-pressure injection under skin may cause serious damage. Excessive exposure may result in eye, skin, or respiratory irritation.

# ENVIRONMENTAL HAZARDS

No significant hazards.

**NOTE:** This material should not be used for any other purpose than the recommended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

# SECTION 3 COMPOSITION AND INFORMATION OF THE INGREDIENTS OF THE HAZARDOUS CHEMICAL

This material is defined as a mixture.

### Hazardous Substance(s) or Complex Substance(s) required for disclosure

Name	CAS#	Concentration*	GHS Hazard Codes
1H-BENZOTRIAZOLE-1-METHANAMINE, N,N-BIS(2- ETHYLHEXYL)-METHYL-	94270-86-7	0.1 - < 1%	H315, H317, H400(M factor 1), H411
BENZENAMINE, N-PHENYL-, REACTION PRODUCTS WITH 2,4,4-TRIMETHYLPENTENE	68411-46-1	1 - < 5%	[H316], [H402], H412
HEXANEDIOIC ACID, DILITHIUM SALT	18621-94-8	1 - < 5%	[H402], H302
LITHIUM HYDROXIDE MONOHYDRATE	1310-66-3	0.1 - < 1%	H302, H314(1B)
NAPHTHENIC ACIDS, ZINC SALTS	12001-85-3	0.1 - < 1%	[H401], H411, H317, H319(2A)
ZINC DIALKYL DITHIOPHOSPHATE	68457-79-4	1 - < 2.5%	[H401], H411, H315, H318

Note - any hazard code in brackets [Hxxx] is a GHS building block that was not adopted by Malaysia in the CLASS Regulation and therefore is not applicable in Malaysia and is shown for informational purposes only.

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.



Product Name: MOBILITH SHC PM 460 Revision Date: 15 Jul 2021 Page 3 of 11

# SECTION 4 FIRST AID MEASURES

#### INHALATION

Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

# SKIN CONTACT

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

#### EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

# INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

# NOTE TO PHYSICIAN

None

#### SECTION 5 FIRE FIGHTING MEASURES

# **EXTINGUISHING MEDIA**

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Inappropriate Extinguishing Media: Straight streams of water

# FIRE FIGHTING

**Fire Fighting Instructions:** Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Hazardous Combustion Products:** Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulphur oxides

# FLAMMABILITY PROPERTIES

Flash Point [Method]: >204°C (399°F) [EST. FOR OIL, ASTM D-92 (COC)] Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D Autoignition Temperature: N/D

# SECTION 6 ACCIDENTAL RELEASE MEASURES

# PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.



Product Name: MOBILITH SHC PM 460 Revision Date: 15 Jul 2021 Page 4 of 11

# PROTECTIVE MEASURES

Avoid contact with spilled material. See Section 6 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 5 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

# **ENVIRONMENTAL PRECAUTIONS**

Prevent entry into waterways, sewers, basements or confined areas.

# METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

**Land Spill:** Allow spilled material to solidify and shovel it up into a suitable container for recycle or disposal. Scrape up spilled material with shovels into a suitable container for recycle or disposal.

**Water Spill:** Stop leak if you can do so without risk. Confine the spill immediately with booms. Warn other shipping. Skim from surface

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

# SECTION 7 HANDLING AND STORAGE

#### PRECAUTIONS FOR SAFE HANDLING

Prevent small spills and leakage to avoid slip hazard.

Static Accumulator: This material is not a static accumulator.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Do not store in open or unlabelled containers.

# SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

# CONTROL PARAMETERS

## **EXPOSURE LIMIT VALUES**

# Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name	Form	Limit/Sta	Indard	Note	Source
LITHIUM HYDROXIDE		Ceiling	1 mg/m3		OARS WEEL
MONOHYDRATE					



Product Name: MOBILITH SHC PM 460 Revision Date: 15 Jul 2021 Page 5 of 11

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

# **Biological limits**

No biological limits allocated.

# **ENGINEERING CONTROLS**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

# PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No protection is ordinarily required under normal conditions of use and with adequate ventilation. Particulate

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

No protection is ordinarily required under normal conditions of use. Nitrile, Viton

**Eye Protection:** If contact is likely, safety glasses with side shields are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

# **ENVIRONMENTAL CONTROLS**

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.



Product Name: MOBILITH SHC PM 460 Revision Date: 15 Jul 2021 Page 6 of 11

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

#### **GENERAL INFORMATION**

Physical State:SolidForm:Semi-fluidColour:Off-WhiteOdour:CharacteristicOdour Threshold:N/D

# IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15 °C): 0.864 Density: 864 kg/m<sup>3</sup> (7.21 lbs/gal, 0.86 kg/dm<sup>3</sup>) Flammability (Solid, Gas): N/A Flash Point [Method]: >204°C (399°F) [EST. FOR OIL, ASTM D-92 (COC)] Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D Autoignition Temperature: N/D **Boiling Point / Range:** N/D Decomposition Temperature: N/D Vapour Density (Air = 1): N/D Vapour Pressure: < 0.013 kPa (0.1 mm Hg) at 20 °C Evaporation Rate (n-butyl acetate = 1): N/D pH: N/A Log Pow (n-Octanol/Water Partition Coefficient): > 3.5 Solubility in Water: Negligible Viscosity: 460 cSt (460 mm2/sec) at 40°C | 55.6 cSt (55.6 mm2/sec) at 100°C **Oxidizing Properties:** See Hazards Identification Section.

# **OTHER INFORMATION**

Freezing Point:N/DMelting Point:N/D

NOTE: Most physical properties above are for the oil component in the material.

#### SECTION 10 STABILITY AND REACTIVITY

**REACTIVITY:** See sub-sections below.

**STABILITY:** Material is stable under normal conditions.

**CONDITIONS TO AVOID:** Excessive heat. High energy sources of ignition.

**INCOMPATIBLE MATERIALS:** Strong oxidisers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.



Product Name: MOBILITH SHC PM 460 Revision Date: 15 Jul 2021 Page 7 of 11

#### **SECTION 11 TOXICOLOGICAL INFORMATION**

# INFORMATION ON TOXICOLOGICAL EFFECTS

Hazard Class	Conclusion / Remarks
Inhalation	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
Ingestion	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin Corrosion/Irritation: Data available. Test scores or other study results do not meet criteria for classification.	Negligible irritation to skin at ambient temperatures. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 404
Eye	
Serious Eye Damage/Irritation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.
Sensitisation	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: No end point data for material.	Not expected to be a skin sensitizer. Based on assessment of the components.
Aspiration: Data available.	Not expected to be an aspiration hazard. Based on physico- chemical properties of the material.
Germ Cell Mutagenicity: No end point data for material.	Not expected to be a germ cell mutagen. Based on assessment of the components.
Carcinogenicity: No end point data for material.	Not expected to cause cancer. Based on assessment of the components.
Reproductive Toxicity: No end point data for material.	Not expected to be a reproductive toxicant. Based on assessment of the components.
Lactation: No end point data for material.	Not expected to cause harm to breast-fed children.
Specific Target Organ Toxicity (STOT)	
Single Exposure: No end point data for material.	Not expected to cause organ damage from a single exposure.
Repeated Exposure: No end point data for material.	Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components.

# TOXICITY FOR SUBSTANCES

NAME	ACUTE TOXICITY
HEXANEDIOIC ACID, DILITHIUM SALT	Oral Lethality: LD 50 1098 mg/kg (Rat)

# **OTHER INFORMATION**

# For the product itself:

Component concentrations in this formulation would not be expected to cause skin sensitization, based on tests of the components, this formulation, or similar formulations. Contains:

Synthetic base oils: Not expected to cause significant health effects under conditions of normal use, based on



Product Name: MOBILITH SHC PM 460 Revision Date: 15 Jul 2021 Page 8 of 11

laboratory studies with the same or similar materials. Not mutagenic or genotoxic. Not sensitising in test animals and humans.

# IARC Classification:

The following ingredients are cited on the lists below: None.

1 = IARC 1--REGULATORY LISTS SEARCHED--<br/>2 = IARC 2A3 = IARC 2B

# SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

#### ECOTOXICITY

Material -- Expected to be harmful to aquatic organisms.

#### **MOBILITY IN SOIL**

Base oil component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY No data available.

BIOACCUMULATIVE POTENTIAL No data available

# **OTHER ADVERSE EFFECTS**

No adverse effects are expected.

# SECTION 13 DISPOSAL INFORMATION

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

#### **DISPOSAL METHODS**

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Suitable routes of disposal are supervised incineration, preferentially with energy recovery, or appropriate recycling methods in accordance with applicable regulations and material characteristics at the time of disposal.

# **REGULATORY DISPOSAL INFORMATION**

#### Environmental Quality (Scheduled Wastes) Regulations 2005 waste code: SW 305

Note: These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste disposal code(s); This material is



Product Name: MOBILITH SHC PM 460 Revision Date: 15 Jul 2021 Page 9 of 11

considered as hazardous waste pursuant to Environmental Quality (Scheduled Wastes) Regulations 2005.

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

# SECTION 14 TRANSPORT INFORMATION

LAND : Not Regulated for Land Transport

**SEA (IMDG):** Not Regulated for Sea Transport according to IMDG-Code

Marine Pollutant: No

**AIR (IATA):** Not Regulated for Air Transport

# SECTION 15 REGULATORY INFORMATION

This material is not hazardous as defined by the Occupational Safety and Health (Classification, Labeling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

# **REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS**

Listed or exempt from listing/notification on the following chemical inventories : AIIC, IECSC, ISHL, KECI, TCSI, TSCA

Special Cases:

Inventory	Status
PICCS	Restrictions Apply

#### National Laws and Regulations:

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000

SECTION 16	OTHER INFORMATION	

#### List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet: Acronym Full text

N/A	Not applicable
N/D	Not determined
NE	Not established
VOC	Volatile Organic Compound
AIIC	Australian Inventory of Industrial Chemicals



Product Name: MOBILITH SHC PM 460 Revision Date: 15 Jul 2021 Page 10 of 11

AIHA WEEL	American Industrial Hygiene Association Workplace Environmental Exposure Limits
ASTM	ASTM International, originally known as the American Society for Testing and Materials (ASTM)
DSL	Domestic Substance List (Canada)
EINECS	European Inventory of Existing Commercial Substances
ELINCS	European List of Notified Chemical Substances
ENCS	Existing and new Chemical Substances (Japanese inventory)
IECSC	Inventory of Existing Chemical Substances in China
KECI	Korean Existing Chemicals Inventory
NDSL	Non-Domestic Substances List (Canada)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances
TLV	Threshold Limit Value (American Conference of Governmental Industrial Hygienists)
TSCA	Toxic Substances Control Act (U.S. inventory)
UVCB	Substances of Unknown or Variable composition, Complex reaction products or Biological materials
LC	Lethal Concentration
LD	Lethal Dose
LL	Lethal Loading
EC	Effective Concentration
EL	Effective Loading
NOEC	No Observable Effect Concentration
NOELR	No Observable Effect Loading Rate

# KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

H302: Harmful if swallowed; Acute Tox Oral, Cat 4

H314(1B): Causes severe skin burns and eye damage; Skin Corr/Irritation, Cat 1B

H315: Causes skin irritation; Skin Corr/Irritation, Cat 2

H316: Causes mild skin irritation; Skin Corr/Irritation, Cat 3

H317: May cause allergic skin reaction; Skin Sensitisation, Cat 1

H318: Causes serious eye damage; Serious Eye Damage/Irr, Cat 1

H319(2A): Causes serious eye irritation; Serious Eye Damage/Irr, Cat 2A

H400: Very toxic to aquatic life; Acute Env Tox, Cat 1

H401: Toxic to aquatic life; Acute Env Tox, Cat 2

H402: Harmful to aquatic life; Acute Env Tox, Cat 3

H411: Toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 2

H412: Harmful to aquatic life with long lasting effects; Chronic Env Tox, Cat 3

# THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

HT LUBRICANT SENDIRIAN BERHAD (646137-M): Section 01: Supplier Mailing Address information was modified. MOBILUB TRADING SENDIRIAN BERHAD (514125-H): Section 01: Supplier Mailing Address information was modified.

OPTIMUM FLUIDS MARKETING SENDIRIAN BERHAD (668909-D): Section 01: Supplier Mailing Address information was modified.

TIMUR LUBE SDN. BHD. (806793-H): Section 01: Supplier Mailing Address information was modified.

Composition: Component Table information was modified.

Section 03: Viscosity information was modified.

Section 15: Special Cases Table information was added.

Section 16: HCode Key information was modified.

\_\_\_\_\_

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer



Product Name: MOBILITH SHC PM 460 Revision Date: 15 Jul 2021 Page 11 of 11

repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly of indirectly hold any interest.

\_\_\_\_\_

DGN: 7052602XMY (1007001)