

Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number: 7108728XCN

Version: 3.02

## SAFETY DATA SHEET

### SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT

**Product Name:** MOBILCUT 210  
**Product Description:** Base Oil and Additives  
**Product Code:** 2015703010J5, 661991-60  
**Recommended Use:** Metal processing fluid

#### COMPANY IDENTIFICATION

**Supplier:** ExxonMobil (China) Investment Co., Ltd.  
17/F., Metro Tower  
30 Tian Yao Qiao Road  
Shanghai 200030 China

**24 Hour Emergency Telephone** (+86) 0532-83889090  
**Supplier General Contact** (+86) 021-34116000  
**E-Mail** consumerservice@mobil.com.cn  
**FAX** (+86) 021-23515968

**Supplier:** EXXONMOBIL CHEMICAL SERVICES (SHANGHAI) CO., LTD  
1099 Zixing Road  
Minhang District  
Shanghai, CN China

**24 Hour Emergency Telephone** (+86) 0532-83889090  
**Supplier General Contact** (+86) 021-34116000  
**E-Mail** consumerservice@mobil.com.cn  
**FAX** (+86) 021-23515968

### SECTION 2 HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW:

**Physical State:** Liquid **Colour:** Amber **Odour:** Characteristic  
H303: May be harmful if swallowed. H315: Causes skin irritation. H318: Causes serious eye damage.  
H402: Harmful to aquatic life.  
High-pressure injection under skin may cause serious damage. Ingestion may cause serious adverse effects

Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number: 7108728XCN

Version: 3.02

and may be fatal. May cause kidney failure and central nervous system effects. Prolonged exposure to elevated concentrations of mist or liquid may cause irritation of the skin, eyes, and respiratory tract.

The hazard classification for this material is in accordance with the General Rules for Classification and Hazard Communication of Chemicals (GB 13690-2009).

**CLASSIFICATION:**

Acute oral toxicant: Category 5. Skin irritation: Category 2. Serious eye damage: Category 1.

Acute aquatic toxicant: Category 3.

**LABEL:**

Symbol:



Signal Word: Danger

**Hazard Statements:**

Health: H303: May be harmful if swallowed. H315: Causes skin irritation. H318: Causes serious eye damage.

Environmental: H402: Harmful to aquatic life.

**Precautionary Statements:**

Prevention: P260: Do not breathe mist / vapours. P264: Wash skin thoroughly after handling. P273: Avoid release to the environment. P280: Wear protective gloves and eye / face protection.

Response: P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER/doctor/physician. P332 + P313: If skin irritation occurs: Get medical advice/attention. P362 + P364: Take off contaminated clothing and wash it before reuse.

Disposal: P501: Dispose of contents and container in accordance with local regulations.

**Contains:** 2-PROPANOL, 1-(2-BUTOXY-1-METHYLETHOXY)-,; 3,3'-METHYLENEBIS (5-METHYLOXAZOLIDINE); ALCOHOLS, C12-C15, ETHOXYLATED; CARBAMIC ACID, BUTYL-, 3-iodo-2-propynyl ester; ETHANOL, 2,2-OXYBIS-; SODIUM PETROLEUM SULPHONATE

**Contains:** 3,3'-METHYLENEBIS (5-METHYLOXAZOLIDINE), CARBAMIC ACID, BUTYL-, 3-iodo-2-propynyl ester May

Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number: 7108728XCN

Version: 3.02

produce an allergic reaction.

## Other hazard information:

## PHYSICAL / CHEMICAL HAZARDS

No significant hazards.

## HEALTH HAZARDS

High-pressure injection under skin may cause serious damage. Ingestion may cause serious adverse effects and may be fatal. May cause kidney failure and central nervous system effects. Prolonged exposure to elevated concentrations of mist or liquid may cause irritation of the skin, eyes, and respiratory tract.

## ENVIRONMENTAL HAZARDS

No additional hazards.

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

This material is defined as a mixture.

### Hazardous Substance(s) or Complex Substance(s) required for disclosure

Name	CAS#	Concentration*	GHS Hazard Codes
2-PROPANOL, 1-(2-BUTOXY-1-METHYLETHOXY)-,	29911-28-2	5 - < 10%	H303
3,3'-METHYLENEBIS (5-METHYLOXAZOLIDINE)	66204-44-2	1 - < 5%	H227, H302, H311, H317, H332, H341, H350(1B), H314(1B), H373, H401, H412
ALCOHOLS, C12-C15, ETHOXYLATED	68131-39-5	1 - < 5%	H318, H400(M factor 1)
BORIC ACID (H3BO3) COMPD. WITH 2,2'-IMINOBIS\{ETHANOL\}	67952-33-4	5 - < 10%	H315, H319(2A)
CARBAMIC ACID, BUTYL-, 3-iodo-2-propynyl ester	55406-53-6	0.1 - < 1%	H302, H317, H331, H318, H372, H400(M factor 10), H410(M factor 1)
ETHANOL, 2,2-OXYBIS-	111-46-6	1 - < 5%	H302
OLEIC ACID-DIETHANOLAMIDE	93-83-4	1 - < 5%	H315, H319(2A), H401, H411
SODIUM PETROLEUM SULPHONATE	68608-26-4	1 - < 5%	H318

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## SECTION 4 FIRST AID MEASURES

Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number:7108728XCN

Version:3.02

**FIRST AID:****INHALATION**

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

**SKIN CONTACT**

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

**EYE CONTACT**

Flush thoroughly with water for at least 15 minutes. Get medical assistance.

**INGESTION**

Seek immediate medical attention.

**IMPORTANT SYMPTOMS AND HEALTH EFFECTS**

Eye pain, redness, tearing, swelling of eyelids, itching. Itching, pain, redness, swelling of skin. Headache, dizziness, drowsiness, nausea and other CNS effects. Abdominal pain, diarrhea, low blood pressure and coma. Local necrosis as evidenced by delayed onset of pain and tissue damage a few hours after injection. Itching and rash from allergic skin reaction.

**ADVICE TO PROTECT RESCUER**

Please refer to Section 8 for personal protection information.

**NOTE TO PHYSICIAN**

This product contains ethylene glycol and/or diethylene glycol which, if ingested, are metabolized to toxic metabolites by the enzyme alcohol dehydrogenase, for which ethanol and 4-methylpyrazole \{U.S. drug name Fomepizole, trade name Antizol\} are antagonists. Administration of oral or intravenous ethanol or intravenous 4-methylpyrazole may arrest further metabolism of this material and thereby ameliorate the toxicity. Use of ethanol or 4-methylpyrazole does not affect toxic metabolites that are already present and is not a substitute for hemodialysis.

Pre-existing conditions which may be aggravated by exposure include emphysema and asthma.

**PRE-EXISTING MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY EXPOSURE**

Pre-existing conditions which may be aggravated by exposure include emphysema and asthma.

**SECTION 5 FIRE FIGHTING MEASURES**

Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number: 7108728XCN

Version: 3.02

## EXTINGUISHING MEDIA

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight streams of water

## SPECIAL HAZARD WHEN ON FIRE

In case of fire, see below for hazardous combustion products. Containers exposed to excessive heat from a fire may rupture.

## FIRE FIGHTING INSTRUCTIONS AND PROTECTIVE MEASURES

### FIRE FIGHTING

**Fire Fighting Instructions:** Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Unusual Fire Hazards:** Pressurised mists may form a flammable mixture. Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

**Hazardous Combustion Products:** Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulphur oxides

## FLAMMABILITY PROPERTIES

**Flash Point [Method]:** >100 C (212 F) [ASTM D-93]

**Flammable Limits (Approximate volume % in air):** LEL: N/D UEL: N/D

**Autoignition Temperature:** N/D

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

### PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number: 7108728XCN

Version: 3.02

## ENVIRONMENTAL PRECAUTIONS

Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

## SPILL MANAGEMENT

**Land Spill:** Stop leak if you can do so without risk. Do not touch or walk through spilled material. Recover by pumping or with suitable absorbent.

**Water Spill:** Stop leak if you can do so without risk. This product emulsifies, disperses or is miscible in water. Remove material, as much as possible, using mechanical equipment.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

## SECTION 7 HANDLING AND STORAGE

### HANDLING

Avoid breathing mists or vapour. Avoid contact with skin. Avoid contact with eyes. Small metal particles from machining may cause abrasion of the skin and may predispose to dermatitis. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or earthing procedures. However, bonding and earthing may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics – Code of practice for the avoidance of hazards due to static electricity).

**Static Accumulator:** This material is a static accumulator.

### STORAGE

The type of container used to store the material may affect static accumulation and dissipation. Do not store in open or unlabelled containers.

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMIT VALUES

Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number:7108728XCN

Version:3.02

**Exposure limits/standards (Note: Exposure limits are not additive)**

Substance Name	Form	Limit/Standard			Note	Source	Year
ETHANOL, 2,2-OXYBIS-		TWA	10 mg/m3			OARS WEEL	2018

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

**ENGINEERING CONTROLS**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

**PERSONAL PROTECTION**

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

Particulate air-purifying respirator approved for dust or oil mist is recommended.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended. Nitrile, Viton

**Eye Protection:** Chemical goggles are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

Chemical/oil resistant clothing is recommended.

Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number:7108728XCN

Version:3.02

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

## ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

**Note:** Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

## GENERAL INFORMATION

**Physical State:** Liquid

**Colour:** Amber

**Odour:** Characteristic

**Odour Threshold:** N/D

## IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

**Relative Density (at 15 °C):** 1

**Flash Point [Method]:** >100 °C (212 °F) [ASTM D-93]

**Flammable Limits (Approximate volume % in air):** LEL: N/D UEL: N/D

**Flammability (Solid, Gas):** N/A

**Autoignition Temperature:** N/D

**Boiling Point / Range:** > 150 °C (302 °F) [Estimated]

**Vapour Density (Air = 1):** > 2 at 101 kPa [Estimated]

**Vapour Pressure:** < 0.013 kPa (0.1 mm Hg) at 20 °C [Estimated]

**Evaporation Rate (n-butyl acetate = 1):** N/D

**pH:** 9.6

**Log Pow (n-Octanol/Water Partition Coefficient):** N/D

**Solubility in Water:** Emulsifies

**Viscosity:** 27 cSt (27 mm<sup>2</sup>/sec) at 40 °C

**Freezing Point:** N/D

**Melting Point:** N/A

**Decomposition Temperature:** N/D

**Oxidizing Properties:** See Hazards Identification Section.

## OTHER INFORMATION

**Pour Point:** -6 °C (21 °F)



Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number: 7108728XCN

Version: 3.02

DMSO Extract (mineral oil only), IP-346: < 3 %wt

## SECTION 10 STABILITY AND REACTIVITY

**STABILITY:** Material is stable under normal conditions.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.

**CONDITIONS TO AVOID:** Heat/ Freezing temperatures. High energy sources of ignition.

**MATERIALS TO AVOID:** Strong Acids, Strong oxidisers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

## SECTION 11 TOXICOLOGICAL INFORMATION

### INFORMATION ON TOXICOLOGICAL EFFECTS

Hazard Class	Conclusion / Remarks
<b>Inhalation</b>	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material.	Elevated temperatures or mechanical action may form vapours, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs.
<b>Ingestion</b>	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
<b>Skin</b>	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin Corrosion/Irritation: No end point data for material.	Irritating to the skin. Based on assessment of the components.
<b>Eye</b>	
Serious Eye Damage/Irritation: No end point data for material.	Irritating and will injure eye tissue. Based on assessment of the components.
<b>Sensitisation</b>	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: No end point data for material.	Contains a substance that may cause skin sensitization. Based on assessment of the components.
<b>Aspiration:</b> Data available.	Not expected to be an aspiration hazard. Based on physico-chemical properties of the material.
<b>Germ Cell Mutagenicity:</b> No end point data for material.	Not expected to be a germ cell mutagen. Based on assessment of the components.
<b>Carcinogenicity:</b> No end point data for	Not expected to cause cancer. Based on assessment of the

Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number: 7108728XCN

Version: 3.02

material.	components.
<b>Reproductive Toxicity:</b> No end point data for material.	Not expected to be a reproductive toxicant. Based on assessment of the components.
<b>Lactation:</b> No end point data for material.	Not expected to cause harm to breast-fed children.
<b>Specific Target Organ Toxicity (STOT)</b>	
Single Exposure: No end point data for material.	Not expected to cause organ damage from a single exposure.
Repeated Exposure: No end point data for material.	Contains a substance that may cause damage to organs from prolonged or repeated exposure. Based on assessment of the components.

## TOXICITY FOR SUBSTANCES

NAME	ACUTE TOXICITY
2-PROPANOL, 1-(2-BUTOXY-1-METHYLETHOXY)-,	Oral Lethality: LD 50 4000 mg/kg (Rat)
ALCOHOLS, C12-C15, ETHOXYLATED	Dermal Lethality: LD 50 2.5 g/kg (Rabbit); Oral Lethality: LD 50 4.150 g/kg (Rat)
CARBAMIC ACID, BUTYL-, 3-iodo-2-propynyl ester	Inhalation Lethality: 4 hour(s) LC50 0.68 mg/l (Aerosol) (Rat); Oral Lethality: LD 50 1056 mg/kg (Rat)

## OTHER INFORMATION

### For the product itself:

Target Organs Repeated Exposure: Kidney

An ingredient or ingredients that are classified as a skin sensitizer.

Oil Mist (highly refined oils): Animals exposed to high concentrations of mist developed oil retention, inflammation, and oil granulomas in the respiratory tract. Oils exposed to high temperatures, cracking conditions, or mixing with tramp / used oils may introduce polycyclic aromatic compounds or microbial contaminants that could result in cancer or severe respiratory hazards.

### Contains:

DIETHYLENE GLYCOL (DEG): Orally, DEG is more toxic to humans than animal test data indicate. Probable lethal dose for an adult is about 50 ml (2 oz.), or 2 -3 swallows. Smaller amounts may cause kidney degeneration and failure. Benign urinary bladder tumours were observed in rats, no tumours were observed in mice. Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitising in test animals.

### IARC Classification:

The following ingredients are cited on the lists below: None.

Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number: 7108728XCN

Version: 3.02

---

--REGULATORY LISTS SEARCHED--

1 = IARC 1

2 = IARC 2A

3 = IARC 2B

## SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

### ECOTOXICITY

Material -- Expected to be harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

### PERSISTENCE AND DEGRADABILITY

#### Biodegradation:

Base oil component -- Expected to be inherently biodegradable

## SECTION 13 DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste disposal code(s).

### DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

## SECTION 14 TRANSPORT INFORMATION

China List of Dangerous Goods (GB 12268 - 2012) : Not Regulated for Land Transport

### INTERNATIONAL CLASSIFICATION FOR TRANSPORT

Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number: 7108728XCN

Version: 3.02

**SEA (IMDG):** Not Regulated for Sea Transport according to IMDG-Code**Marine Pollutant:** No**AIR (IATA):** Not Regulated for Air Transport

## SECTION 15 REGULATORY INFORMATION

The hazard classification for this material is in accordance with the General Rules for Classification and Hazard Communication of Chemicals (GB 13690-2009).

### REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS

**The General Rules for preparation of precautionary label for Chemicals (GB 15258-2009):**  
Regulated

**Law of the People's Republic of China on Prevention and Control of Environmental Pollution by Solid Waste:** See Disposal Considerations section.

**Listed or exempt from listing/notification on the following chemical inventories :** AIIC, IECSC

## SECTION 16 OTHER INFORMATION

N/D = Not determined, N/A = Not applicable

**KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):**

H302: Harmful if swallowed; Acute Tox Oral, Cat 4

H312: Harmful in contact with skin; Acute Tox Dermal, Cat 4

H314(1B): Causes severe skin burns and eye damage; Skin Corr/Irritation, Cat 1B

H315: Causes skin irritation; Skin Corr/Irritation, Cat 2

H317: May cause allergic skin reaction; Skin Sensitisation, Cat 1

H318: Causes serious eye damage; Serious Eye Damage/Irr, Cat 1

H319(2A): Causes serious eye irritation; Serious Eye Damage/Irr, Cat 2A

H331: Toxic if inhaled; Acute Tox Inh, Cat 3

H372: Causes damage to organs through prolonged or repeated exposure; Target Organ, Repeated, Cat 1

H373: May cause damage to organs through prolonged or repeated exposure; Target Organ, Repeated, Cat 2

H400: Very toxic to aquatic life; Acute Env Tox, Cat 1

H402: Harmful to aquatic life; Acute Env Tox, Cat 3

H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1

### THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

EXXONMOBIL CHEMICAL SERVICES (SHANGHAI) CO., LTD: Section 01: Supplier Mailing Address information was added.

Product Name: MOBILCUT 210

Revision Date: 17 May 2021

Issue Date: 5 Nov 2015

SDS Number: 7108728XCN

Version: 3.02

---

Composition: Component Table information was modified.

GHS Health Symbol information was modified.

Section 01: Company Contact Methods information was modified.

Section 02: GHS Sensitizer Statement information was modified.

Section 08: Exposure Limits Table information was modified.

Section 10: Conditions to Avoid information was modified.

Section 11 Substance Toxicology table information was modified.

Section 11: Target Organ Toxicity Repeat - Organ Systems information was added.

Section 13: National Catalogue of Hazardous Wastes information was deleted.

Section 13: Disposal Recommendations - Note information was modified.

Section 15: National Chemical Inventory Listing information was modified.

Section 16: HCode Key information was modified.

Section 16: Revision Information - SDS format change phrase. information was deleted.

---

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

(AP Core)

---

DGN: 7108728XCN (1014186)

---